ISO 16000-23:2009-12 (E)

Indoor air - Part 23: Performance test for evaluating the reduction of formaldehyde concentrations by sorptive buildin g materials

Contents

Page

Foreword iv

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols 4

5 Principle 5

6 Apparatus and materials 5

7 Test conditions 6
7.1 General 6
7.2 Test conditions for concentration reduction performance determination 7
7.3 Factors affecting the concentration reduction performance 8

8 Verification of test conditions 8
8.1 Monitoring of test conditions 8
8.2 Air tightness of test chamber 8
8.3 Air change rate in test chamber 8
8.4 Efficiency of the internal test chamber air mixing 9
8.5 Recovery 9

9 Preparation of test chamber 9

10 Preparation of test specimens 9
11 Test methods 9
11.1 Background concentration and spiked supply air 9
11.2 Placing the test specimen in the test chamber 9
11.3 Time intervals for measurement of test chamber concentration 10
11.4 Air sampling 10
12 Determination of formaldehyde 10
13 Expression of results 11
13.1 Calculation of sorption flux 11
13.2 Calculation of equivalent ventilation rate per area 11
13.3 Calculation of total mass per area of sorption and saturation mass per area 11
14 Test report 11

Annex A (normative) Sample tube test for long-term reduction performance 14

Annex B (normative) System for quality assurance and quality control 18

Annex C (informative) Example measurements of construction materials 20

Annex D (informative) Long-term reduction performance (example procedure) 25

Bibliography 28