

DIN EN 14625:2012-12 (E)

Ambient air - Standard method for the measurement of the concentration of ozone by ultraviolet photometry

Contents		Page
Contents 2		
Foreword		4
1 Scope		5
2 Normative references		6
3 Terms and definitions		6
4 Abbreviated terms		11
5 Principle		11
5.1 General		11
5.2 Measuring principle		11
5.3 Type approval test		12
5.4 Field operation and quality control		12
6 Sampling		12
6.1 General		12
6.2 Sampling location		13
6.3 Sampling system		13
6.4 Control and regulation of sample flow rate		14
6.5 Sampling pump for the manifold		14
7 Analyser equipment		14
7.1 General		14
7.2 Ultraviolet absorption cell		15
7.3 Ultraviolet source lamp		15
7.4 UV detector		15
7.5 Ozone-specific scrubber		15
7.6 Switching valve		15
7.7 Temperature indicator		15
7.8 Pressure indicator		15
7.9 Flow rate indicator		16
7.10 Sampling pump for the analyser		16
7.11 Internal ozone span source		16
7.12 Particle filter		16
8 Type approval of ultraviolet photometric ozone analysers		16
8.1 General		16
8.2 Relevant performance characteristics and performance criteria		17
8.3 Design change		18
8.4 Procedures for determination of the performance characteristics during the laboratory test		19
8.5 Determination of the performance characteristics during the field test		30
8.6 Type approval and uncertainty calculation		33
9 Field operation and ongoing quality control		34
9.1 General		34
9.2 Suitability evaluation		34

9.3	Initial installation	36
9.4	Ongoing quality assurance/quality control	37
9.5	Calibration of the analyser	38
9.6	Checks	40
9.7	Maintenance	44
9.8	Data handling and data reports	44
9.9	Measurement uncertainty	45
10	Expression of results	45
11	Test reports and documentation	45
11.1	Type approval test	45
11.2	Field operation	47
Annex A (normative) Test of lack of fit		48
Annex B (informative) Sampling equipment		50
Annex C (informative) Ultraviolet photometric analyser		52
Annex D (informative) Manifold testing equipment		54
Annex E (normative) Type approval		56
Annex F (informative) Calculation of uncertainty in field operation at the hourly alert threshold value		75
Annex G (informative) Calculation of uncertainty in field operation at the 8-hour target value		83
Annex H (informative) Significant technical changes		93
Bibliography		94