DIN ISO 16000-24:2013-01 (E)

Indoor air - Part 24: Performance test for evaluati ng the reduction of volatile organic compound (except formaldehyde) concentrations by sorptive building materials (ISO 16000-24:2009)

Contents

Page

National foreword 3

National Annex NA (informative) Bibliography 5

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions 9

4 Symbols 11

5 Principle 11

6 Apparatus and materials 12

7 Test conditions 13
7.1 General 13
7.2 Test conditions for concentration reduction performance determination 14
7.3 Factors affecting the concentration reduction performance 15

8 Verification of test conditions 15
8.1 Monitoring of test conditions 15
8.2 Air-tightness of test chamber 15
8.3 Air change rate in test chamber 16
8.4 Efficiency of the internal test chamber air mixing 16
8.5 Recovery 16

9 Preparation of test chamber 16

10 Preparation of test specimens 16

11 Test methods 16
11.1 Background concentration and spiked supply air 16
11.2 Placing the test specimen in the test chamber 17
11.3 Time intervals for measurement of chamber concentration 17
11.4 Air sampling 17

12 Determination of target compounds 18

13 Expression of results 18
13.1 Calculation of sorption flux 18
13.2 Calculation of equivalent ventilation rate per area 18
13.3 Calculation of total mass per area of sorption and saturation mass per area 18

14 Test report 19

Annex A (normative) Sample tube test for long-term reduction performance 21

Annex B (normative) System for quality assurance and quality control 25

Bibliography 27