

DIN ISO 16000-24:2013-01 (E)

Indoor air - Part 24: Performance test for evaluating the reduction of volatile organic compound (except formaldehyde) concentrations by sorptive building materials (ISO 16000-24:2009)

Contents		Page
National foreword		3
National Annex NA (informative) Bibliography		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	9
4	Symbols	11
5	Principle	11
6	Apparatus and materials	12
7	Test conditions	13
7.1	General	13
7.2	Test conditions for concentration reduction performance determination	14
7.3	Factors affecting the concentration reduction performance	15
8	Verification of test conditions	15
8.1	Monitoring of test conditions	15
8.2	Air-tightness of test chamber	15
8.3	Air change rate in test chamber	16
8.4	Efficiency of the internal test chamber air mixing	16
8.5	Recovery	16
9	Preparation of test chamber	16
10	Preparation of test specimens	16
11	Test methods	16
11.1	Background concentration and spiked supply air	16
11.2	Placing the test specimen in the test chamber	17
11.3	Time intervals for measurement of chamber concentration	17
11.4	Air sampling	17
12	Determination of target compounds	18
13	Expression of results	18
13.1	Calculation of sorption flux	18
13.2	Calculation of equivalent ventilation rate per area	18
13.3	Calculation of total mass per area of sorption and saturation mass per area	18
14	Test report	19

Annex A (normative) Sample tube test for long-term reduction performance	21
Annex B (normative) System for quality assurance and quality control	25
Bibliography	27