

ISO 12219-3:2012-06 (E)

Interior air of road vehicles - Part 3: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Micro-scale chamber method

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Principle	2
5 Apparatus	2
6 Test conditions	3
6.1 Temperature	4
6.2 Air or gas flow rate through the micro-scale chamber	4
6.3 Quality of supplied air or gas and background concentration of organic vapours	4
6.4 Control measures	4
7 Test specimens	4
7.1 General	4
7.2 Preparation of the test specimen	5
8 Cleaning micro-scale chamber components	5
9 Test method	5
9.1 Sampling media	5
9.2 Measuring background concentrations	6
9.3 Vapour sampling	6
9.4 Sealing the vapour sampling devices after gas sample collection	6
9.5 Analysis of vapour sampling devices	6
9.6 Storage of the test specimen between emissions tests (if required)	6
9.7 Cleaning the micro-scale chamber after use	6
10 Calculation of vapour concentrations and specific emission rates	7
11 Test report	8
12 Quality assurance/quality control	9
Annex A (informative) Micro-scale chamber principles	10
Annex B (informative) Micro-scale chamber -- Example 1	12
Annex C (informative) Micro-scale chamber -- Example 2	14
Annex D (informative) Micro-scale chamber -- Example 3	16

Annex E (informative) Assessment of VOC recoveries	18
Annex F (informative) Calculation of specific emission rates from micro-scale chamber air concentration	19
Bibliography	21