

ISO 12219-3:2012-06 (E)

Interior air of road vehicles - Part 3: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Micro-scale chamber method

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Principle | 2 |
| 5 | Apparatus | 2 |
| 6 | Test conditions | 3 |
| 6.1 | Temperature | 4 |
| 6.2 | Air or gas flow rate through the micro-scale chamber | 4 |
| 6.3 | Quality of supplied air or gas and background concentration of organic vapours | 4 |
| 6.4 | Control measures | 4 |
| 7 | Test specimens | 4 |
| 7.1 | General | 4 |
| 7.2 | Preparation of the test specimen | 5 |
| 8 | Cleaning micro-scale chamber components | 5 |
| 9 | Test method | 5 |
| 9.1 | Sampling media | 5 |
| 9.2 | Measuring background concentrations | 6 |
| 9.3 | Vapour sampling | 6 |
| 9.4 | Sealing the vapour sampling devices after gas sample collection | 6 |
| 9.5 | Analysis of vapour sampling devices | 6 |
| 9.6 | Storage of the test specimen between emissions tests (if required) | 6 |
| 9.7 | Cleaning the micro-scale chamber after use | 6 |
| 10 | Calculation of vapour concentrations and specific emission rates | 7 |
| 11 | Test report | 8 |
| 12 | Quality assurance/quality control | 9 |
| Annex A (informative) Micro-scale chamber principles | | 10 |
| Annex B (informative) Micro-scale chamber -- Example 1 | | 12 |
| Annex C (informative) Micro-scale chamber -- Example 2 | | 14 |
| Annex D (informative) Micro-scale chamber -- Example 3 | | 16 |

| | |
|--|-----------|
| Annex E (informative) Assessment of VOC recoveries | 18 |
| Annex F (informative) Calculation of specific emission rates from micro-scale chamber air concentration | 19 |
| Bibliography | 21 |