ISO 12219-3:2012-06 (E)

Interior air of road vehicles - Part 3: Screening method for the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Micro-scale chamber method

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Principle 2

5 Apparatus 2

6 Test conditions 3
6.1 Temperature 4
6.2 Airorgasflowratethroughthemicro-scalechamber 4
6.3 Quality of supplied air or gas and background concentration of organic vapours 4
6.4 Control measures 4

7 Test specimens 4
7.1 General 4
7.2 Preparation of the test specimen 5

8 Cleaning micro-scale chamber components 5

9 Test method 5
9.1 Sampling media 5
9.2 Measuring background concentrations 6
9.3 Vapour sampling 6
9.4 Sealing the vapour sampling devices after gas sample collection 6
9.5 Analysis of vapour sampling devices 6
9.6 Storage of the test specimen between emissions tests (if required) 6
9.7 Cleaning the micro-scale chamber after use 6

10 Calculationofvapourconcentrationsandspecificemissionrates 7

11 Test report 8

12 Quality assurance/quality control 9

Annex A (informative) Micro-scale chamber principles 10

Annex B (informative) Micro-scale chamber -- Example 1 12

Annex C (informative) Micro-scale chamber -- Example 2 14

Annex D (informative) Micro-scale chamber -- Example 3 16

Annex E (informative) Assessment of VOC recoveries 18

Annex F (informative)Calculationofspecificemissionratesfrommicro-scalechamber air concentration 19

Bibliography 21