

DIN ISO 12219-2:2012-11 (E)

Interior air of road vehicles - Part 2: Screening method f or the determination of the emissions of volatile organic compounds from vehicle interior parts and materials - Bag method (ISO 12219-2:2012)

Contents

| | Page |
|--|------|
| National foreword | 3 |
| National Annex NA (informative) Bibliography | |
| Introduction | 7 |
| 1 Scope | 8 |
| 2 Normative references | 8 |
| 3 Terms and definitions | 8 |
| 4 Principle | 9 |
| 5 Apparatus and materials | 9 |
| 6 Test conditions | 11 |
| 6.1 General | 11 |
| 6.2 Test specimen size | 11 |
| 6.3 Curing conditions (storage period and storage conditions) | 11 |
| 6.4 Heating temperature | 11 |
| 6.5 Heating time | 11 |
| 6.6 Gas amount to be filled in a sampling bag | 11 |
| 7 Verification of test conditions | 12 |
| 7.1 Monitoring of test conditions | 12 |
| 7.2 Recovery rate | 12 |
| 8 Test method | 12 |
| 8.1 Test equipment | 12 |
| 8.2 Preparation for testing | 12 |
| 8.3 Emission test | 12 |
| 8.4 Gas collection | 13 |
| 9 Analytical procedures | 13 |
| 9.1 Analysis of VOCs | 13 |
| 9.2 Analysis of formaldehyde and other carbonyl compounds | 13 |
| 10 Calculation of sampling bag values | 14 |
| 11 Test report | 14 |
| 12 Quality assurance/quality control | 15 |
| Annex A (informative) General procedures for preparation and storage of test specimens | 18 |
| Annex B (informative) Additional information on test report and recovery rate | 19 |
| Bibliography | 21 |