

DIN ISO 16000-28:2012-12 (E)

Indoor air - Part 28: Determination of odour emissions from building products using test chambers (ISO 16000-28:2012)

Contents		Page
	4
Introduction	9
1	Scope	10
2	Normative references	10
3	Terms, definitions, symbols, units and abbreviated terms	10
3.1	Terms and definitions	10
3.2	Symbols and units	13
3.3	Abbreviated terms	13
4	Principle	14
5	Test facilities	14
5.1	General	14
5.2	Apparatus	14
5.3	Test chamber and equipment materials	15
5.4	Air supply and mixing facilities	15
5.5	Airtightness	15
5.6	Odour sampling and assessment devices	15
6	Test conditions	16
6.1	General	16
6.2	Temperature and relative humidity in the test chamber	17
6.3	Supply air quality and background concentration in the test chamber	17
6.4	Air velocity in the test chamber	17
6.5	Area-specific air flow rate and air exchange rate in the test chamber	17
6.6	Test chamber airtightness	18
6.7	Efficiency of the internal test chamber air mixing	18
6.8	Test chamber and test room background odour	18
7	Test specimens	10
8	Odour testing from emission chamber	20
8.1	Test chamber preparation	20
8.2	Test specimen location in the test chamber	20
8.3	Time of odour measurements	20
9	Odour panels	20
9.1	Panel leader	20
9.2	Panel selection	21
9.3	Code of behaviour of the panel members	21
9.4	Panel size and accuracy of the evaluation	21
10	Odour assessment	22
10.1	General	22
10.2	Acceptability using an untrained panel	22
10.3	Perceived odour intensity	23
10.4	Complementary method – Hedonic tone using an untrained panel	24

11	Test report	24
	AnnexA(normative)Systemforqualityassurance/qualitycontrol	26
	AnnexB(informative)Statisticalbackground	27
	AnnexC(informative)Examplesofdiffuserandmaskusedforodoureevaluation	29