

# DIN ISO 16000-28:2012-12 (E)

## Indoor air - Part 28: Determination of odour emissions from building products using test chambers (ISO 16000-28:2012)

---

<b>Contents</b>		<b>Page</b>
	.....	4
<b>Introduction</b>	.....	<b>9</b>
<b>1</b>	<b>Scope</b> .....	<b>10</b>
<b>2</b>	<b>Normative references</b> .....	<b>10</b>
<b>3</b>	<b>Terms, definitions, symbols, units and abbreviated terms</b> .....	<b>10</b>
<b>3.1</b>	<b>Terms and definitions</b> .....	<b>10</b>
<b>3.2</b>	<b>Symbols and units</b> .....	<b>13</b>
<b>3.3</b>	<b>Abbreviated terms</b> .....	<b>13</b>
<b>4</b>	<b>Principle</b> .....	<b>14</b>
<b>5</b>	<b>Test facilities</b> .....	<b>14</b>
<b>5.1</b>	<b>General</b> .....	<b>14</b>
<b>5.2</b>	<b>Apparatus</b> .....	<b>14</b>
<b>5.3</b>	<b>Test chamber and equipment materials</b> .....	<b>15</b>
<b>5.4</b>	<b>Air supply and mixing facilities</b> .....	<b>15</b>
<b>5.5</b>	<b>Airtightness</b> .....	<b>15</b>
<b>5.6</b>	<b>Odour sampling and assessment devices</b> .....	<b>15</b>
<b>6</b>	<b>Test conditions</b> .....	<b>16</b>
<b>6.1</b>	<b>General</b> .....	<b>16</b>
<b>6.2</b>	<b>Temperature and relative humidity in the test chamber</b> .....	<b>17</b>
<b>6.3</b>	<b>Supply air quality and background concentration in the test chamber</b> .....	<b>17</b>
<b>6.4</b>	<b>Air velocity in the test chamber</b> .....	<b>17</b>
<b>6.5</b>	<b>Area-specific air flow rate and air exchange rate in the test chamber</b> .....	<b>17</b>
<b>6.6</b>	<b>Test chamber airtightness</b> .....	<b>18</b>
<b>6.7</b>	<b>Efficiency of the internal test chamber air mixing</b> .....	<b>18</b>
<b>6.8</b>	<b>Test chamber and test room background odour</b> .....	<b>18</b>
<b>7</b>	<b>Test specimens</b> .....	<b>10</b>
<b>8</b>	<b>Odour testing from emission chamber</b> .....	<b>20</b>
<b>8.1</b>	<b>Test chamber preparation</b> .....	<b>20</b>
<b>8.2</b>	<b>Test specimen location in the test chamber</b> .....	<b>20</b>
<b>8.3</b>	<b>Time of odour measurements</b> .....	<b>20</b>
<b>9</b>	<b>Odour panels</b> .....	<b>20</b>
<b>9.1</b>	<b>Panel leader</b> .....	<b>20</b>
<b>9.2</b>	<b>Panel selection</b> .....	<b>21</b>
<b>9.3</b>	<b>Code of behaviour of the panel members</b> .....	<b>21</b>
<b>9.4</b>	<b>Panel size and accuracy of the evaluation</b> .....	<b>21</b>
<b>10</b>	<b>Odour assessment</b> .....	<b>22</b>
<b>10.1</b>	<b>General</b> .....	<b>22</b>
<b>10.2</b>	<b>Acceptability using an untrained panel</b> .....	<b>22</b>
<b>10.3</b>	<b>Perceived odour intensity</b> .....	<b>23</b>
<b>10.4</b>	<b>Complementary method – Hedonic tone using an untrained panel</b> .....	<b>24</b>

<b>11</b>	<b>Test report .....</b>	<b>24</b>
	<b>AnnexA(normative)Systemforqualityassurance/qualitycontrol .....</b>	<b>26</b>
	<b>AnnexB(informative)Statisticalbackground .....</b>	<b>27</b>
	<b>AnnexC(informative)Examplesofdiffuserandmaskusedforodourevaluation .....</b>	<b>29</b>