

DIN ISO 12219-6:2017-08 (E)

Interior air of road vehicles - Part 6: Method for the determination of the emissions of semi-volatile organic compounds from vehicle interior parts and materials at higher temperature - Small chamber method (ISO 12219-6:2017)

Contents

	Page
National foreword	4
National Annex (informative) Bibliography	6
Foreword	9
Introduction	10
1 Scope	11
2 Normative references	11
3 Terms and definitions	12
4 Symbols	12
5 Principle	12
6 Emission test bed preparation	13
6.1 General	13
6.2 Small chamber	13
6.2.1 General	13
6.2.2 Materials	13
6.2.3 Tightness	14
6.2.4 Air mixing	14
6.2.5 Cleaning	14
6.3 Small chamber temperature control	14
6.4 Air humidification	14
6.5 Clean air supply	15
7 Quality control	15
7.1 General	15
7.2 Airtightness	16
7.2.1 General	16
7.2.2 Alternative procedure 1	16
7.2.3 Alternative procedure 2	16
7.3 Recovery and sink effects	16
7.4 Supply air	17
7.4.1 General	17
7.4.2 Background concentration values	17
7.4.3 Temperature and humidity	18
8 Test specimen	18
8.1 General	18
8.2 History of the test specimen	18
8.3 Packaging, transport and storage of the test specimen	18
9 Standard emission test procedure	19
9.1 General	19
9.2 Cleaning and purification	19
9.3 Test	19
9.3.1 General	19
9.3.2 Preconditioning the sample prior to test	19
9.3.3 Preparation	20
9.3.4 Cleaning — Phase 1	20
9.3.5 Preconditioning — Phase 2	20
9.3.6 Background concentration sampling — Phase 3	20

9.3.7	Inserting the test specimen — Phase 4	20
9.3.8	Conditioning at 65 °C — Phase 5 according to ISO 12219-4	20
9.3.9	Heating up and conditioning at 100 °C — Phase 6	20
9.3.10	Air sampling at 100 °C — Phase 7	21
9.3.11	End of testing	21
10	Determination of VOCs at 65 °C and SVOCs at 100 °C in one run	22
11	Calculation of the emission rate	22
12	Test report	22
13	Quality assurance/quality control (QA/QC)	24
Annex A (informative) Typical test conditions and example for the experimental setup	25	
Bibliography	27	