

DIN EN 13284-1:2018-02 (E)

Stationary source emissions - Determination of low range mass concentration of dust - Part 1: Manual gravimetric method

Contents		Page
European foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	Symbols and abbreviations	9
4.1	Symbols	9
4.2	Abbreviations	10
5	Principle	10
6	Measurement planning and sampling strategy	11
6.1	Measurement planning	11
6.2	Sampling strategy	12
6.2.1	General	12
6.2.2	Measurement section and measurement plane	12
6.2.3	Minimum number and location of measurement points	12
6.2.4	Measurement ports and working platform	12
7	Equipment and materials	12
7.1	Gas velocity, temperature, pressure and composition measurement devices	12
7.2	Sampling equipment	12
7.2.1	Sampling system	12
7.2.2	Filtration device	13
7.2.3	Entry nozzle	17
7.2.4	Suction tube for out-stack filtration devices	18
7.2.5	Suction unit	18
7.2.6	Gas metering devices	18
7.3	Dust deposit recovery accessories	20
7.4	Equipment for conditioning and weighing	20
8	Weighing procedure	20
8.1	General	20
8.2	Pre-sampling conditioning	20
8.3	Weighing	21
8.4	Post-sampling treatment of weighed parts	21
8.5	Post-sampling treatment of the rinsing solutions	22
8.6	Improvement of the weighing procedure	22
9	Sampling procedure	22
9.1	Preparation	22
9.2	Filter handling	23
9.3	Pre-measurements	23
9.4	Leak test	24
9.5	Sampling	24
9.6	Recovery of deposits upstream of the filter	26
9.6.1	General	26
9.6.2	Rinsing procedure	26

9.7	Field blank	26
10	Calculation	27
10.1	Sampling volumetric flow rate	27
10.2	Dust concentration	27
11	Measurement report	28
Annex A (informative) Performance characteristics of the method obtained in the method validation		30
A.1	General	30
A.2	Experimental data	31
A.3	Comments	31
Annex B (informative) Influence of the isokinetic rate on the representativeness of the collected particles		33
Annex C (informative) Proven design of the entry nozzles		37
Annex D (informative) Summary of the requirements		40
Annex E (normative) Sampling volume, flow rate and duration		42
E.1	General	42
E.2	Weighing uncertainties	42
E.3	Sampling volume	42
E.4	Sampling flow rate and duration	42
Annex F (informative) Examples of weighing bias		43
F.1	General	43
F.2	Effect of insufficient temperature equilibrium	43
F.3	Effect of temperature variations	43
F.4	Effect of barometric pressure variations	43
F.5	Conclusions	44
Annex G (informative) Determination of the measurement uncertainty		45
G.1	General	45
G.2	Principle of the determination of the uncertainty contributions of measurands	45
G.2.1	General	45
G.2.2	Uncertainty contribution of calibration	45
G.2.3	Uncertainty contribution of the drift	46
G.2.4	Uncertainty contribution of the display resolution	46
G.3	Combination of the uncertainty contributions of the individual measurands	47
G.3.1	Procedure	47
G.3.2	Specification of the method model equation	48
G.3.3	Stepwise calculation of the individual uncertainty contributions	49
G.4	Effective number of the degrees of freedom	58
Annex H (informative) Thermal behaviour of dusts		60
Annex I (informative) Significant technical changes		61
Bibliography		63