

ISO 9096:2017-09 (E)

Stationary source emissions - Manual determination of mass concentration of particulate matter

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	4
4.1	General	4
4.2	Interferences	5
5	Sampling plane and sampling points	5
5.1	General	5
5.2	Sampling plane	6
5.3	Requirements for sampling points	6
5.4	Minimum number and location of sampling points	6
5.5	Access ports	7
5.6	Sampling time	7
6	Apparatus and materials	8
6.1	Gas velocity, temperature, pressure, and gas composition measurement devices	8
6.2	Sampling apparatus	8
6.3	Material for particulate matter recovery	14
6.4	Apparatus for conditioning and weighing	14
7	Sampling and weighing procedures	15
7.1	General aspects	15
7.2	Weighing procedure	16
7.2.1	Parts to be weighed	16
7.2.2	Pre-sampling treatment of weighed parts	16
7.2.3	Weighing	16
7.2.4	Post-sampling treatment of weighed parts	17
7.2.5	Post-sampling treatment of the rinsing solutions	17
7.3	Sampling	18
7.3.1	Preparation	18
7.3.2	Pre-measurements	18
7.3.3	Calculating the nozzle diameter	18
7.3.4	Overall blank	20
7.3.5	Sampling procedure	20
7.3.6	Recovery of deposits upstream of the filter	21
7.4	Validation of results	21
7.4.1	Parameters depending on the stationary source	21
7.4.2	Leak check	21
7.4.3	Isokinetic flowrate	22
7.4.4	Deposits of dust on non-weighed parts upstream of the filter	22
7.4.5	Validation of sample collection	22
7.4.6	Summary of the requirements of this document	22

8	Additional aspects	22
8.1	Thermal behaviour of particulate matter	22
8.2	Particulate deposits upstream of the filter	24
8.3	Improvement of the weighing procedure	24
9	Calculations	25
9.1	Isokinetic flowrate	25
9.2	Dust concentration	25
9.2.1	General	25
9.2.2	Oxygen correction factor	26
9.2.3	Carbon dioxide correction factor	26
10	Performance characteristics	26
10.1	General aspects	26
10.2	Experimental data for sampling	27
11	Test report	27
	Annex A (normative) Proven design of the entry nozzle	29
	Annex B (normative) Determination of positions of sampling points in circular and rectangular ducts	30
	Annex C (informative) Examples of weighing bias	34
	Annex D (informative) Isokinetic sampling conditions	36
	Annex E (informative) Summary validation information	38
	Annex F (informative) Examples of suitable access ports for sampling equipment	41
	Bibliography	43