ISO 16000-34:2018 (E)

Indoor air — Part 34: Strategies for the measurement of airborne particles

Contents

Foreword

Introduction

1 Scope

5

- 2 Normative references
- 3 Terms and definitions
- 4 Origin, properties and health implications of airborne particles
 - 4.1 Origin and properties
 - 4.2 Health implications

Sources of indoor particulate matter and particle dynamics indoors

- 5.1 General
- 5.2 Sources of indoor particulate matter
- 5.2.1 Typical indoor sources
- 5.2.2 Influence of the premises
- 5.2.3 Particle size range generated by typical sources
- 5.3 Particle dynamics indoors
- 5.3.1 Major particle sinks
- 5.3.2 Variations of the particle spectrum
- 5.3.3 Effect of air conditioning
- 5.3.4 Conditions of room use
- 6 Measurement methods for airborne particles indoors
 - 6.1 General
 - 6.2 Established method description
 - 6.2.1 General
 - 6.2.2 Cyclone
 - 6.2.2.1 Principle
 - 6.2.2.2 Capabilities of the method
 - 6.2.2.3 Limits of the method
 - 6.2.3 Impactors (impactor cascade impactor LPI MOI)
 - 6.2.3.1 Principle
 - 6.2.3.2 Capabilities of the method
 - 6.2.3.3 Limits of the method
 - 6.2.4 Differential mobility analyser (DMA)
 - 6.2.4.1 Principle
 - 6.2.4.2 Capabilities of the method
 - 6.2.4.3 Limits of the method
 - 6.2.5 Aerosol mass spectrometer (AMS)
 - 6.2.5.1 Principle
 - 6.2.5.2 Capabilities of the method
 - 6.2.5.3 Limits of the method
 - 6.2.6 Aerosol mass monitor (AMM)
 - 6.2.6.1 Principle
 - 6.2.6.2 Capabilities of the method
 - 6.2.6.3 Limits of the method
 - 6.2.7 Oscillating microbalance (OMB)
 - 6.2.7.1 Principle
 - 6.2.7.2 Capabilities of the method
 - 6.2.7.3 Limits of the method
 - 6.2.8 Beta radiation attenuation (BRA) monitor

- 6.2.8.1 Principle
- 6.2.8.2 Capabilities of the method
- 6.2.8.3 Limits of the method
- 6.2.9 Microscopy (OM SEM TEM)
- 6.2.9.1 Principle
- 6.2.9.2 Capabilities of the method
- 6.2.9.3 Limits of the method
- 6.2.10 Light scattering aerosol spectrometer (LSAS)
- 6.2.10.1 Principle
- 6.2.10.2 Capabilities of the method
- 6.2.10.3 Limits of the method 6.2.11 Time-of-flight spectrometer (TOF-AS)
- 6.2.11.1 Principle
- 6.2.11.2 Capabilities of the method
- 6.2.11.2.1 Limits of the method
- 6.2.12 Condensation particle counter (CPC UF CPC CPC with SES CPC photometric mode)
- 6.2.12.1 Principle
- 6.2.12.2 Capabilities of the method
- 6.2.12.3 Limits of the method
- 6.2.13 Faraday cup aerosol electrometer (FCAE)
- 6.2.13.1 Principle
- 6.2.13.2 Capabilities of the method
- 6.2.13.3 Limits of the method
- 6.2.14 Fast response aerosol spectrometer (FRAS)
- 6.2.14.1 Principle
- 6.2.14.2 Capabilities of the method
- 6.2.14.3 Limits of the method
- 6.2.15 Low pressure impactor with electric detection (LPI+E)
- 6.2.15.1 Principle
- 6.2.15.2 Capabilities of the method
- 6.2.15.3 Limits of the method
- 7 General sampling recommendations
 - 7.1 Instrumentation and sampling system
 - 7.2 Measurement location
 - 7.3 Measurement time and duration
 - 7.4 Estimated concentration scale (minimum and maximum accuracy)
 - 7.5 Background concentration
 - 7.6 Impact of outdoor air quality
 - 7.7 Impact of room conditions
 - 7.8 Impact of the measurement itself
 - Measurement strategy for determining airborne particles indoors
 - 8.1 General

8

- 8.2 Preliminary work Definition of the measurement objective and list of basic information
- 8.2.1 General
- 8.2.2 Statement on the purpose of the measurement
- 8.2.3 List of main expected sources
- 8.2.4 Temporal effects
- 8.2.5 Description of the indoor compartment
- 8.3 Visual room inspection Definition of the measurement planning and strategy
- 8.4 Preliminary measurements
- 8.5 Measurement procedures
- 8.5.1 General
- 8.5.2 Procedure for the determination of the background
- 8.5.2.1 Instrumentation and measurands
- 8.5.2.2 Measurement procedure
- 8.5.2.3 Measurement planning and setup
- 8.5.2.4 Evaluation
- 8.5.3 Procedure for the estimation of the influence of outdoor (ambient air) concentration
- 8.5.3.1 Instrumentation and measurands
- 8.5.3.2 Measurement procedure

- 8.5.3.3 Measurement planning and setup
- 8.5.3.4 Evaluation
- 8.5.4 Procedure for the identification of main sources present in a room
- 8.5.4.1 General
- 8.5.4.2 Instrumentation and measurands
- 8.5.4.3 Measurement procedure
- 8.5.4.4 Measurement planning and setup
- 8.5.4.5 Evaluation
- 8.5.5 Procedure for the measurement of the average and the time-resolved emission of a specific source
- 8.5.5.1 General
- 8.5.5.2 Instrumentation and measurands
- 8.5.5.3 Measurement procedure
- 8.5.5.4 Measurement planning and setup
- 8.5.5.5 Evaluation
- 8.5.6 Procedure for the estimation of the efficiency of an abatement techniques (i.e. filtration by air conditioning system
- 8.5.6.1 General
- 8.5.6.2 Instrumentation and measurands
- 8.5.6.3 Measurement procedure
- 8.5.6.4 Measurement planning and setup
- 8.5.6.5 Evaluation
- 9 Uncertainty evaluation
- 10 Evaluation and reporting of results
- 11 Documentation
- 12 Quality assurance
 - 12.1 Performance specifications
 - 12.2 Quality assurance when determining particle number concentrations
 - 12.2.1 General
 - 12.2.2 Sampling volume flow
 - 12.2.3 Checking the equipment's parameters
 - 12.3 Quality assurance when determining particle mass concentrations
 - 12.3.1 Mass concentration calculation based on measured number concentration
 - 12.3.2 Gravimetric mass concentration measurement
 - 12.3.2.1 General
 - 12.3.2.2 Flow control system
 - 12.3.2.3 Weighing system
- Annex A (normative) Protocol for the measurement of indoor airborne particles

Page count: 47