

DIN ISO 28902-3:2019-04 (E)

Air quality - Environmental meteorology - Part 3: Ground-based remote sensing of wind by continuous-wave Doppler lidar (ISO 28902-3 :2018)

Contents	Page
National foreword	3
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	6
4 Fundamentals of heterodyne Doppler lidar	9
4.1 Overview	9
4.2 Heterodyne detection	10
4.3 Spectral analysis	12
4.3.1 Signal processing for CW lidar	12
4.3.2 An example of a wind speed estimation process	14
4.4 Target variables	14
4.5 Sources of noise and uncertainties	14
4.5.1 Local oscillator shot noise	14
4.5.2 Detector noise	15
4.5.3 Relative intensity noise	15
4.5.4 Speckles	15
4.5.5 Laser frequency	15
4.6 Range assignment	15
4.7 Known limitations	16
5 System specifications and tests	17
5.1 System specifications	17
5.1.1 Laser wavelength	17
5.1.2 Transmitter/receiver characteristics	17
5.1.3 Pointing system characteristics	17
5.2 Figures of merit	18
5.3 Precision and availability of measurements	18
5.3.1 Radial velocity measurement accuracy	18
5.3.2 Data availability	19
5.3.3 Maximum operational range	19
5.4 Testing procedures	19
5.4.1 General	19
5.4.2 Hard target return	19
5.4.3 Assessment of accuracy by intercomparison with other instrumentation	19
5.4.4 Maximum operational range validation	21
6 Measurement planning and installation instructions	21
6.1 Site requirements	21
6.2 Limiting conditions for general operation	22
6.3 Maintenance and operational test	22
6.3.1 General	22
6.3.2 Maintenance	22
6.3.3 Operational test	22
6.3.4 Uncertainty	23
Bibliography	24