

# ISO 16000-9:2024-03 (E)

## Indoor air - Part 9: Determination of the emission of volatile organic compounds from samples of building products and furnishing - Emission test chamber method

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>		<b>iv</b>
<b>Introduction</b>		<b>v</b>
<b>1 Scope</b>		<b>1</b>
<b>2 Normative references</b>		<b>1</b>
<b>3 Terms and definitions</b>		<b>1</b>
<b>4 Symbols and abbreviated terms</b>		<b>3</b>
4.1 Symbols		3
4.2 Abbreviated terms		4
<b>5 Principle</b>		<b>4</b>
<b>6 Emission test chamber system</b>		<b>4</b>
6.1 General		4
6.2 Emission test chamber materials		4
6.3 Air supply and mixing facilities		4
6.4 Air tightness		5
6.5 Air sampling devices		5
6.6 Recovery and sink effects		5
<b>7 Apparatus</b>		<b>5</b>
<b>8 Test conditions</b>		<b>6</b>
8.1 Temperature and relative air humidity		6
8.2 Supply air quality and background concentration		6
8.3 Air velocity		6
8.4 Area specific air flow rate and air change rate		6
<b>9 Verification of the test conditions</b>		<b>7</b>
9.1 General		7
9.2 Temperature and relative air humidity control systems		7
9.3 Air change rate in the emission test chamber		7
9.4 Emission test chamber air tightness		7
9.5 Air velocity in the emission test chamber		7
9.6 Efficiency of the internal emission test chamber air mixing		7
<b>10 Test specimens</b>		<b>8</b>
<b>11 Emission test chamber preparation</b>		<b>8</b>
<b>12 Test method</b>		<b>8</b>
12.1 Background concentrations		8
12.2 Test specimen location in the emission test chamber		8
12.3 Time for measurements of test chamber air concentration		8
<b>13 Calculation of area specific emission rates and expression of results</b>		<b>9</b>
<b>14 Performance characteristics</b>		<b>9</b>
<b>15 Test report</b>		<b>9</b>
<b>Annex A (normative) System for quality assurance and quality control</b>		<b>11</b>
<b>Annex B (informative) Examples of loading factors for a model room</b>		<b>13</b>
<b>Annex C (informative) General description of an emission test chamber</b>		<b>14</b>
<b>Annex D (informative) Determination of the emission rates of seams and cut edges</b>		<b>15</b>
<b>Bibliography</b>		<b>16</b>