

ISO 16000-9:2024-03 (E)

Indoor air - Part 9: Determination of the emission of volatile organic compounds from samples of building products and furnishing - Emission test chamber method

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	3
4.1	Symbols	3
4.2	Abbreviated terms	4
5	Principle	4
6	Emission test chamber system	4
6.1	General	4
6.2	Emission test chamber materials	4
6.3	Air supply and mixing facilities	4
6.4	Air tightness	5
6.5	Air sampling devices	5
6.6	Recovery and sink effects	5
7	Apparatus	5
8	Test conditions	6
8.1	Temperature and relative air humidity	6
8.2	Supply air quality and background concentration	6
8.3	Air velocity	6
8.4	Area specific air flow rate and air change rate	6
9	Verification of the test conditions	7
9.1	General	7
9.2	Temperature and relative air humidity control systems	7
9.3	Air change rate in the emission test chamber	7
9.4	Emission test chamber air tightness	7
9.5	Air velocity in the emission test chamber	7
9.6	Efficiency of the internal emission test chamber air mixing	7
10	Test specimens	8
11	Emission test chamber preparation	8
12	Test method	8
12.1	Background concentrations	8
12.2	Test specimen location in the emission test chamber	8
12.3	Time for measurements of test chamber air concentration	8
13	Calculation of area specific emission rates and expression of results	9
14	Performance characteristics	9
15	Test report	9
Annex A (normative)	System for quality assurance and quality control	11
Annex B (informative)	Examples of loading factors for a model room	13
Annex C (informative)	General description of an emission test chamber	14
Annex D (informative)	Determination of the emission rates of seams and cut edges	15
Bibliography		16