

ISO 12141:2024-09 (E)

Stationary source emissions - Determination of low range mass concentration of dust - Manual gravimetric method

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Symbols and abbreviations | 5 |
| 4.1 | Symbols | 5 |
| 4.2 | Abbreviations | 5 |
| 5 | Principle | 6 |
| 6 | Measurement planning and sampling strategy | 6 |
| 6.1 | Measurement planning | 6 |
| 6.2 | Sampling strategy | 7 |
| 6.2.1 | General | 7 |
| 6.2.2 | Measurement section and measurement plane | 7 |
| 6.2.3 | Minimum number and location of measurement points | 7 |
| 6.2.4 | Measurement ports and working platform | 7 |
| 7 | Equipment and materials | 8 |
| 7.1 | Gas velocity, temperature, pressure and composition measurement devices | 8 |
| 7.2 | Sampling equipment | 8 |
| 7.2.1 | Sampling system | 8 |
| 7.2.2 | Filtration device | 8 |
| 7.2.3 | Entry nozzle | 12 |
| 7.2.4 | Suction tube for out-stack filtration devices | 12 |
| 7.2.5 | Suction unit | 12 |
| 7.2.6 | Gas metering devices | 12 |
| 7.3 | Dust deposit recovery accessories | 14 |
| 7.4 | Equipment for conditioning and weighing | 14 |
| 8 | Weighing procedure | 14 |
| 8.1 | General | 14 |
| 8.2 | Pre-sampling conditioning | 14 |
| 8.3 | Weighing | 15 |
| 8.4 | Post-sampling treatment of weighed parts | 15 |
| 8.5 | Post-sampling treatment of the rinsing solutions | 16 |
| 8.6 | Improvement of the weighing procedure | 16 |
| 9 | Sampling procedure | 16 |
| 9.1 | Preparation | 16 |
| 9.2 | Filter handling | 17 |
| 9.3 | Pre-measurements | 17 |
| 9.4 | Leak test | 18 |
| 9.5 | Sampling | 18 |
| 9.6 | Recovery of deposits upstream of the filter | 19 |

| | | |
|---|-------------------------------------|----|
| 9.6.1 | General | 19 |
| 9.6.2 | Rinsing procedure | 20 |
| 9.7 | Field blank | 20 |
| 10 | Calculation | 20 |
| 10.1 | Sampling volumetric flow rate | 20 |
| 10.2 | Dust concentration | 21 |
| 11 | Measurement report | 21 |
| Annex A (informative) Performance characteristics of the method obtained in the method validation | | 23 |
| Annex B (informative) Influence of the isokinetic rate on the representativeness of the collected particles | | 25 |
| Annex C (informative) Proven design of the entry nozzles | | 31 |
| Annex D (informative) Summary of the requirements | | 33 |
| Annex E (normative) Sampling volume, flow rate and duration | | 34 |
| Annex F (informative) Examples of weighing bias | | 35 |
| Annex G (informative) Determination of the measurement uncertainty | | 37 |
| Annex H (informative) Thermal behaviour of dusts | | 51 |
| Annex I (informative) Significant technical changes | | 52 |
| Bibliography | | 53 |