

DIN EN 14625:2025-12 (E)

Ambient air - Standard method for the measurement of the concentration of ozone by ultraviolet photometry

Contents		Page
European foreword		8
1	Scope	9
2	Normative references	10
3	Terms and definitions	10
4	Abbreviated terms	16
5	Principle	16
5.1	General	16
5.2	Measuring principle	16
5.3	Type testing	17
5.4	Field operation and quality control	18
6	Sampling	18
6.1	General	18
6.2	Sampling location	19
6.3	Sampling system	19
6.3.1	Construction	19
6.3.2	Particle filter	19
6.4	Loss of ozone	20
6.5	Control and regulation of sample flow rate	20
6.6	Sampling pump for the manifold	20
7	Analyser equipment	20
7.1	General	20
7.2	Ultraviolet absorption cell	21
7.3	Ultraviolet source lamp	21
7.4	UV detector	21
7.5	Ozone-specific scrubber	21
7.6	Switching valve	21
7.7	Temperature indicator	22
7.8	Pressure indicator	22
7.9	Flow rate indicator	22
7.10	Sampling pump for the analyser	22
7.11	Internal ozone span source	22
7.12	Particle filter	22
8	Type testing of ultraviolet photometric ozone analysers	22
8.1	General	22
8.2	Relevant performance characteristics and performance criteria	23
8.3	Design change	27
8.4	Procedures for determination of the performance characteristics during the laboratory test	27
8.4.1	General	27
8.4.2	Test conditions	27
8.4.3	Response time	29
8.4.4	Short-term drift	31
8.4.5	Repeatability standard deviation	32

8.4.6	Lack of fit of linearity of the calibration function	32
8.4.7	Sensitivity coefficient to sample gas pressure	33
8.4.8	Sensitivity coefficient to sample gas temperature	34
8.4.9	Sensitivity coefficient to the surrounding temperature	34
8.4.10	Sensitivity coefficient to electrical voltage	35
8.4.11	Interferents	36
8.4.12	Averaging test	36
8.4.13	Difference sample/calibration port	37
8.4.14	Residence time in the analyser	38
8.5	Determination of the performance characteristics during the field test	38
8.5.1	General	38
8.5.2	Selection of a monitoring station for the field test	38
8.5.3	Operational requirements	39
8.5.4	Long-term drift	40
8.5.5	Reproducibility standard deviation under field conditions	40
8.5.6	Period of unattended operation	41
8.5.7	Period of availability of the analyser	41
8.6	Type testing and uncertainty calculation	42
9	Field operation and ongoing quality control	42
9.1	General	42
9.2	Suitability evaluation	43
9.2.1	General	43
9.2.2	Analyser for a monitoring station or task	43
9.3	Initial installation	44
9.4	Ongoing quality assurance/quality control	46
9.4.1	General	46
9.4.2	Frequency of calibrations, checks and maintenance	47
9.5	Calibration of the analyser	50
9.5.1	General	50
9.5.2	Calibration gases	51
9.5.3	Data adjustment function	51
9.5.4	Testing the sampling system	51
9.5.5	Treatment of data after exceedance of performance criteria	53
9.6	Checks	55
9.6.1	Zero and span checks	55
9.6.2	Lack of fit	56
9.6.3	Testing the sample manifold	57
9.7	Maintenance	58
9.7.1	Change of particle filters	58
9.7.2	Maintenance of sampling system	58
9.7.3	Change of consumables as applicable	58
9.7.4	Preventive/routine maintenance of components of the analyser	58
9.8	Data handling and data reports	59
9.9	Measurement uncertainty	59
10	Expression of results	59
11	Test reports and documentation	60
11.1	Type testing	60
11.2	Field operation	61
11.2.1	Suitability evaluation	61
11.2.2	Documentation	61
11.2.3	Ambient air quality data reports	61
Annex A (normative)	Test of lack of fit	63
A.1	Establishment of the regression line	63
A.2	Calculation of the residuals of the averages	64
Annex B (informative)	Sampling equipment	65

Annex C (informative) Ultraviolet photometric analyser	67
Annex D (informative) Manifold testing	69
D.1 Procedure for applying test gas	69
D.2 Procedure for the cross test	70
D.2.1 General	70
D.2.2 Initial stage	70
D.2.3 Stage 1	71
D.2.4 Stage 2	71
D.2.5 Data Processing	71
D.2.6 Evaluation	71
Annex E (normative) Type testing	73
E.1 Type testing and uncertainty calculation	73
E.1.1 Type testing	73
E.1.2 Uncertainty calculation	73
E.2 Type testing Requirement a)	73
E.3 Type testing Requirement b)	75
E.3.1 General	75
E.3.2 Calculation of standard uncertainties	78
E.3.2.1 General	78
E.3.2.2 Repeatability at zero	78
E.3.2.3 Repeatability at the hourly alert threshold value of ozone	78
E.3.2.4 Lack of fit	79
E.3.2.5 Influence quantities	79
E.3.2.5.1 General	79
E.3.2.5.2 Sample gas pressure	80
E.3.2.5.3 Sample gas temperature	80
E.3.2.5.4 Surrounding temperature	80
E.3.2.5.5 Electrical voltage	81
E.3.2.5.6 Water vapour	81
E.3.2.5.7 Other interferences	82
E.3.2.5.8 Averaging effect	83
E.3.2.5.9 Calibration gas	83
E.3.2.5.10 Difference sample/calibration port	83
E.3.3 Example calculation	84
E.4 Type testing Requirement c)	85
E.5 Type testing Requirement d)	85
E.5.1 General	85
E.5.2 Combined standard uncertainty	87
E.5.3 Absolute expanded uncertainty	87
E.5.4 Relative expanded uncertainty	87
E.5.5 Calculation of standard uncertainties	88
E.5.6 Example calculation	90
Annex F (informative) Calculation of uncertainty in field operation at the hourly alert threshold value	92
F.1 General	92
F.2 Combined standard uncertainty	92
F.3 Standard uncertainties	93
F.3.1 General	93
F.3.1.1 Introduction	93
F.3.1.2 Repeatability at zero	93
F.3.1.3 Repeatability at the hourly alert threshold value	93
F.3.1.4 Lack of fit	93
F.3.2 Influence quantities	94
F.3.2.1 General	94
F.3.2.2 Sample gas pressure	94
F.3.2.3 Sample gas temperature	94

F.3.2.4	Surrounding temperature	95
F.3.2.5	Electrical voltage	96
F.3.3	Interferents	96
F.3.3.1	General	96
F.3.3.2	Water vapour	96
F.3.3.3	Other interferents	97
F.3.4	Averaging effect	97
F.3.5	Reproducibility under field conditions	97
F.3.6	Long-term drift at zero	97
F.3.7	Long-term drift at level of the hourly alert threshold value	98
F.3.8	Zero gas	98
F.3.9	Calibration gas	98
F.3.10	Difference sample/calibration port	98
F.4	Example calculation	99
Annex G (informative) Calculation of uncertainty in field operation at the 8-hour target value		101
G.1	General	101
G.2	Combined standard uncertainty	101
G.3	Standard uncertainties	102
G.3.1	General	102
G.3.1.1	Introduction	102
G.3.1.2	Repeatability at zero	102
G.3.1.3	Repeatability at the 8-hour target value	103
G.3.1.4	Lack of fit	103
G.3.2	Influence quantities	103
G.3.2.1	General	103
G.3.2.2	Sample gas pressure	104
G.3.2.3	Sample gas temperature	104
G.3.2.4	Surrounding temperature	105
G.3.2.5	Electrical voltage	105
G.3.3	Interferents	106
G.3.3.1	General	106
G.3.3.2	Water vapour	106
G.3.3.3	Other interferents	107
G.3.4	Averaging effect	108
G.3.5	Zero gas	108
G.3.6	Calibration gas	108
G.3.7	Difference sample/calibration port	108
G.3.8	Reproducibility under field conditions	108
G.3.9	Long-term drift at zero	109
G.3.10	Long-term drift at level of the 8-hour target value	109
G.4	Example calculation	110
Annex H (informative) Test stand for the test point "sensitivity coefficient of sample gas pressure"		112
Annex I (informative) Significant changes		113
Bibliography		114