

# ISO 12219-12:2025-05 (E)

## Interior air of road vehicles - Part 12: Test methods for the determination of fogging characteristics of trim materials made from polyvinyl chloride (PVC) or polyurethane in the interior of automobiles

---

<b>Contents</b>		<b>Page</b>
Foreword		iv
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions</b>	<b>1</b>
<b>4</b>	<b>Principle</b>	<b>1</b>
<b>5</b>	<b>Apparatus and materials</b>	<b>2</b>
<b>6</b>	<b>Sample preparation</b>	<b>5</b>
<b>7</b>	<b>Conditioning</b>	<b>6</b>
<b>8</b>	<b>Procedure</b>	<b>6</b>
8.1	Cleaning	6
8.1.1	General	6
8.1.2	Cleaning with a dishwasher	6
8.1.3	Manual cleaning	6
8.1.4	Polishing of glass surface	6
8.2	Reference tests	6
8.3	Placement of test specimens	7
8.4	Measurements prior to the fogging test	7
8.5	Fogging test	7
8.5.1	Set-up	7
8.5.2	Determination of the fogging value, $F$	8
8.5.3	Determination of the mass of condensable constituents, $G$	8
<b>9</b>	<b>Expression of results</b>	<b>9</b>
9.1	Fogging value	9
9.2	Mass of condensable constituents	9
<b>10</b>	<b>Test report</b>	<b>9</b>
<b>Annex A (informative) Comparison of air chamber and oil bath test results</b>		<b>11</b>
<b>Annex B (informative) Confirmation of fogging test bath accuracy by DIDP</b>		<b>13</b>
<b>Annex C (informative) Effect of polishing glass plate surface</b>		<b>14</b>
<b>Bibliography</b>		<b>16</b>