

ISO 12219-12:2025-05 (E)

Interior air of road vehicles - Part 12: Test methods for the determination of fogging characteristics of trim materials made from polyvinyl chloride (PVC) or polyurethane in the interior of automobiles

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 1 |
| 5 | Apparatus and materials | 2 |
| 6 | Sample preparation | 5 |
| 7 | Conditioning | 6 |
| 8 | Procedure | 6 |
| 8.1 | Cleaning | 6 |
| 8.1.1 | General | 6 |
| 8.1.2 | Cleaning with a dishwasher | 6 |
| 8.1.3 | Manual cleaning | 6 |
| 8.1.4 | Polishing of glass surface | 6 |
| 8.2 | Reference tests | 6 |
| 8.3 | Placement of test specimens | 7 |
| 8.4 | Measurements prior to the fogging test | 7 |
| 8.5 | Fogging test | 7 |
| 8.5.1 | Set-up | 7 |
| 8.5.2 | Determination of the fogging value, F | 8 |
| 8.5.3 | Determination of the mass of condensable constituents, G | 8 |
| 9 | Expression of results | 9 |
| 9.1 | Fogging value | 9 |
| 9.2 | Mass of condensable constituents | 9 |
| 10 | Test report | 9 |
| Annex A (informative) Comparison of air chamber and oil bath test results | | 11 |
| Annex B (informative) Confirmation of fogging test bath accuracy by DIDP | | 13 |
| Annex C (informative) Effect of polishing glass plate surface | | 14 |
| Bibliography | | 16 |