

ISO 12219-12:2025-05 (E)

Interior air of road vehicles - Part 12: Test methods for the determination of fogging characteristics of trim materials made from polyvinyl chloride (PVC) or polyurethane in the interior of automobiles

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	1
5	Apparatus and materials	2
6	Sample preparation	5
7	Conditioning	6
8	Procedure	6
8.1	Cleaning	6
8.1.1	General	6
8.1.2	Cleaning with a dishwasher	6
8.1.3	Manual cleaning	6
8.1.4	Polishing of glass surface	6
8.2	Reference tests	6
8.3	Placement of test specimens	7
8.4	Measurements prior to the fogging test	7
8.5	Fogging test	7
8.5.1	Set-up	7
8.5.2	Determination of the fogging value, F	8
8.5.3	Determination of the mass of condensable constituents, G	8
9	Expression of results	9
9.1	Fogging value	9
9.2	Mass of condensable constituents	9
10	Test report	9
Annex A (informative) Comparison of air chamber and oil bath test results		11
Annex B (informative) Confirmation of fogging test bath accuracy by DIDP		13
Annex C (informative) Effect of polishing glass plate surface		14
Bibliography		16