

DIN EN 14792:2006-04 (E)

Stationary source emissions - Determination of mass concentration of nitrogen oxides (NO<(Index)x>) - Reference method: Chemiluminescence

| Contents | Page |
|---|------|
| Foreword | 4 |
| 1 Scope | 5 |
| 2 Normative references | 5 |
| 3 Terms and definitions | 6 |
| 4 Principle | 10 |
| 4.1 General | 10 |
| 4.2 Measuring principle | 10 |
| 5 Description of measuring equipment - Sampling and sample gas conditioning systems ... | 11 |
| 5.1 General | 11 |
| 5.2 Sampling line components | 12 |
| 5.2.1 Sampling line | 12 |
| 5.2.2 Filter | 12 |
| 5.2.3 Sample cooler (configuration 1) | 12 |
| 5.2.4 Permeation drier (configuration 2) | 12 |
| 5.2.5 Dilution system (configuration 3) | 13 |
| 5.2.6 Heated line and heated analyser (configuration 4) | 13 |
| 5.2.7 Sample pump | 13 |
| 5.2.8 Secondary filter | 13 |
| 5.2.9 Flow controller and flow meter | 13 |
| 6 Analyser equipment | 14 |
| 6.1 General | 14 |
| 6.2 Converter | 14 |
| 6.3 Ozone generator | 14 |
| 6.4 Reaction chamber | 15 |
| 6.5 Optical filter | 15 |
| 6.6 Photomultiplier tube | 15 |
| 6.7 Ozone removal | 15 |
| 7 Determination of the characteristics of the SRM: analyser, sampling and conditioning line | 15 |
| 7.1 General | 15 |
| 7.2 Relevant performance characteristics of the SRM and performance criteria | 16 |
| 7.3 Establishment of the uncertainty budget | 17 |
| 8 Field operation | 18 |
| 8.1 Sampling location | 18 |
| 8.2 Sampling point(s) | 18 |
| 8.3 Choice of the measuring system | 19 |
| 8.4 Setting of the SRM on site | 19 |
| 8.4.1 General | 19 |
| 8.4.2 Preliminary zero and span check, and adjustments | 20 |
| 8.4.3 Zero and span checks after measurement | 20 |
| 9 Ongoing quality control | 21 |
| 9.1 General | 21 |

| | | |
|-------|---|----|
| 9.2 | Frequency of checks | 21 |
| 10 | Expression of results | 22 |
| 11 | Evaluation of the method in the field | 23 |
| 12 | Equivalence with an alternative method | 23 |
| 13 | Test report | 24 |
| | Annex A (informative) Four different sampling and conditioning configurations | 25 |
| | Annex B (normative) Determination of converter efficiency | 26 |
| B.1 | General | 26 |
| B.2 | First method : cylinder gases for calibration | 26 |
| B.3 | Second method : gaseous phase titration | 26 |
| | Annex C (informative) Examples of different types of converters | 28 |
| C.1 | Quartz converter | 28 |
| C.2 | Low temperature converter (molybdenum) | 28 |
| C.3 | Stainless steel converter | 28 |
| | Annex D (informative) Example of assessment of compliance of chemiluminescence method for NOx with requirements on emission measurements | 29 |
| D.1 | General | 29 |
| D.2 | Process of uncertainty estimation | 29 |
| D.2.1 | Determination of the model equation | 29 |
| D.2.2 | Quantification of uncertainty components | 29 |
| D.2.3 | Calculation of the combined uncertainty | 29 |
| D.3 | Specific conditions in the field | 30 |
| D.4 | Performance characteristics of the method | 31 |
| D.4.1 | NO measurement | 32 |
| D.4.2 | NOx measurement | 38 |
| D.4.3 | Results of standard uncertainties calculation | 40 |
| D.4.4 | Calculation of combined uncertainties | 42 |
| D.5 | Conversion of the concentrations in mg/m | 42 |
| D.5.1 | No measurement | 43 |
| D.5.2 | NO₂ measurement | 43 |
| D.5.3 | NOx measurement | 43 |
| D.5.4 | Combined uncertainty | 43 |
| D.5.5 | Overall uncertainty | 43 |
| D.6 | Evaluation of the compliance with the required measurement quality | 43 |
| | Annex E (informative) Procedure of correction of data from drift effect | 45 |
| | Annex F (informative) Evaluation of the method in the field | 46 |
| F.1 | General | 46 |
| F.2 | Characteristics of installations | 46 |
| F.3 | Repeatability and reproducibility in the field | 47 |
| F.3.1 | General | 47 |
| F.3.2 | Repeatability | 48 |
| F.3.3 | Reproducibility | 49 |
| | Annex ZA (informative) Relationship with EU Directives | 50 |
| | Bibliography | 51 |