

DIN EN 14792:2006-04 (E)

Stationary source emissions - Determination of mass concentration of nitrogen oxides (NO_x) - Reference method: Chemiluminescence

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	Principle	10
4.1	General	10
4.2	Measuring principle	10
5	Description of measuring equipment - Sampling and sample gas conditioning systems ...	11
5.1	General	11
5.2	Sampling line components	12
5.2.1	Sampling line	12
5.2.2	Filter	12
5.2.3	Sample cooler (configuration 1)	12
5.2.4	Permeation drier (configuration 2)	12
5.2.5	Dilution system (configuration 3)	13
5.2.6	Heated line and heated analyser (configuration 4)	13
5.2.7	Sample pump	13
5.2.8	Secondary filter	13
5.2.9	Flow controller and flow meter	13
6	Analyser equipment	14
6.1	General	14
6.2	Converter	14
6.3	Ozone generator	14
6.4	Reaction chamber	15
6.5	Optical filter	15
6.6	Photomultiplier tube	15
6.7	Ozone removal	15
7	Determination of the characteristics of the SRM: analyser, sampling and conditioning line	15
7.1	General	15
7.2	Relevant performance characteristics of the SRM and performance criteria	16
7.3	Establishment of the uncertainty budget	17
8	Field operation	18
8.1	Sampling location	18
8.2	Sampling point(s)	18
8.3	Choice of the measuring system	19
8.4	Setting of the SRM on site	19
8.4.1	General	19
8.4.2	Preliminary zero and span check, and adjustments	20
8.4.3	Zero and span checks after measurement	20
9	Ongoing quality control	21
9.1	General	21

9.2	Frequency of checks	21
10	Expression of results	22
11	Evaluation of the method in the field	23
12	Equivalence with an alternative method	23
13	Test report	24
Annex A (informative) Four different sampling and conditioning configurations		25
Annex B (normative) Determination of converter efficiency		26
B.1	General	26
B.2	First method : cylinder gases for calibration	26
B.3	Second method : gaseous phase titration	26
Annex C (informative) Examples of different types of converters		28
C.1	Quartz converter	28
C.2	Low temperature converter (molybdenum)	28
C.3	Stainless steel converter	28
Annex D (informative) Example of assessment of compliance of chemiluminescence method for NO _x with requirements on emission measurements		29
D.1	General	29
D.2	Process of uncertainty estimation	29
D.2.1	Determination of the model equation	29
D.2.2	Quantification of uncertainty components	29
D.2.3	Calculation of the combined uncertainty	29
D.3	Specific conditions in the field	30
D.4	Performance characteristics of the method	31
D.4.1	NO measurement	32
D.4.2	NO _x measurement	38
D.4.3	Results of standard uncertainties calculation	40
D.4.4	Calculation of combined uncertainties	42
D.5	Conversion of the concentrations in mg/m	42
D.5.1	No measurement	43
D.5.2	NO ₂ measurement	43
D.5.3	NO _x measurement	43
D.5.4	Combined uncertainty	43
D.5.5	Overall uncertainty	43
D.6	Evaluation of the compliance with the required measurement quality	43
Annex E (informative) Procedure of correction of data from drift effect		45
Annex F (informative) Evaluation of the method in the field		46
F.1	General	46
F.2	Characteristics of installations	46
F.3	Repeatability and reproducibility in the field	47
F.3.1	General	47
F.3.2	Repeatability	48
F.3.3	Reproducibility	49
Annex ZA (informative) Relationship with EU Directives		50
Bibliography		51