

DIN EN 817:2008-09 (E)

Sanitary tapware - Mechanical mixing valves (PN 10) - General technical specifications

Contents	Page
Foreword	6
Introduction	7
1 Scope	8
2 Normative references	10
3 Terms, definitions and designation	10
3.1 Terms and definitions	10
3.2 Designation	11
4 Marking and identification	11
4.1 Marking	11
4.2 Identification	12
5 Materials	12
5.1 Chemical and hygiene requirements	12
5.2 Exposed surface conditions	12
6 Dimensional characteristics	12
6.1 General remarks	12
6.2 Inlet dimensions	12
6.3 Outlet dimensions	17
6.4 Mounting dimensions	19
6.5 Special cases	20
6.6 Flexible hoses for shower outlets	20
6.7 Shower outlets	20
7 Sequence of testing	21
8 Leaktightness characteristics	21
8.1 General	21
8.2 Test methods	21
8.3 Leaktightness of the obturator and of the mixing valve upstream of the obturators with the obturator in the closed position	22
8.4 Leaktightness of the mixing valve downstream of the obturator with the obturator open ..	22
8.5 Leaktightness of manually operated diverter	22
8.6 Leaktightness and operation of diverter with automatic return	23
8.7 Leaktightness of the obturator: cross flow between hot water and cold water	24
9 Pressure resistance characteristics - mechanical performance under pressure	26
9.1 General	26
9.2 Principle	26
9.3 Apparatus	26
9.4 Mechanical behaviour upstream of the obturator - obturator in the closed position	26
9.5 Mechanical behaviour downstream of the obturator - obturator in the open position	26
10 Hydraulic characteristics	27
10.1 General	27
10.2 Initial settings	27

10.3	Principle	28
10.4	Apparatus	28
10.5	Procedure	28
10.6	Determination of flow rate	29
10.7	Determination of sensitivity	30
11	Mechanical strength characteristics - torsion test for operating mechanism	33
11.1	General	33
11.2	Test method	33
12	Mechanical endurance characteristics	34
12.1	Mechanical endurance of the control device	34
12.2	Mechanical endurance of diverters	38
12.3	Mechanical endurance of swivel spouts	40
13	Backflow protection	41
14	Acoustic characteristics	41
14.1	General	41
14.2	Procedure	41
14.3	Requirements	41
	Bibliography	50
	Annex A (informative) Apparatus	43
	Annex B (informative) Pressure take-off tee	47
	Figures Figure 1 Supply system with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar]	9
	Figure 2 Flexible hoses and plain tube	14
	Figure 3 Multi-hole mechanical mixing valve	15
	Figure 4 Supply connections for mechanical mixing valve and remote outlets	16
	Figure 5 Remote outlet	18
	Figure 6 Single hole mechanical mixing valve	18
	Figure 7 Two hole mechanical mixing valve	18
	Figure 8 Single hole mechanical mixing valve	19
	Figure 9 Two hole mechanical mixing valve	20
	Figure 10 Sensitivity curve	31
	Figure 11 Radius for the determination of sensitivity	32
	Figure 12 Rectangular movement	34
	Figure 13 Triangular movement	35
	Figure 14 Test bench adjustment torque for conventionnal mixing valve	37
	Figure 15 Test bench adjustment torque for joystick mixing valve	37
	Figure 16 Test bench adjustment torque for sequential mixing valve	37
	Figure A 1 Supply circuits	43

Figure A 2 Test circuit	45
Figure A 3 Mounting of the mixing valve	46
Figure B 1 Pressure take-off tee	47
Figure B 2 Schematic examples of pressure take-off tees	48
Tables Table 1 Conditions of use/Classifications	8
Table 2 Designation	11
Table 3 Inlet dimensions (mechanical mixing valve)	13
Table 4 Outlet dimensions (Remote outlets, mechanical mixing valve)	17
Table 5 Mounting dimensions (Outlets, single- and multi-hole mechanical mixing valve)	19
Table 6 Test Sequence	21
Table 7 Summary of leaktightness tests	25
Table 8 Summary of pressure resistance characteristic tests	27
Table 9 Initial Settings	27
Table 10 Flow rates according to application	29
Table 11 Performance levels	30
Table 12 Summary of test conditions for cartridges	35
Table 13 Summary of test conditions for diverters	39
Table 14 Flow rate classes (EN ISO 3822-4 Annex A)	41
Table 15 Acoustic group	42
Table A 1 Connecting dimension	45
Table B 1 Dimensions of the pressure take-off tee	47