DIN EN 15714-4:2010-02 (E)

Industrial valves - Actuators - Part 4: Hydraulic part-turn actuators for industrial valves - Basic requirements

Contents

Page

Foreword 4

1 Scope 5

2 Normative references 5

3 Classification and designation 5
3.1 General 5
3.2 Action 6
3.3 Valve actuator attachment 6
3.4 Motive energy 6
3.4.1 Operating medium 6
3.4.2 Quality 6
3.4.3 Pressure 6

4 Design requirements 6
4.1 General 6
4.2 Output torques (performance test) 7
4.3 Pressure ratings and endurance 7
4.3.1 Pressure ratings 7
4.3.2 Endurance 7
4.4 Minimum moving pressure 8
4.5 Leakage 8
4.6 Moving time 8
4.7 Angle 9
4.8 Fluid displacement volume 9
4.9 Environmental conditions 9
4.9.1 Ambient temperature 9
4.9.2 Enclosure protection 9
4.9.3 Corrosion protection 9
4.10 Basic design 10
4.10.1 Safety requirements 10
4.10.2 Part-turn valve actuator attachment 10
4.10.3 Pressure connections 11
4.10.4 Fail safe direction for spring return actuators 12
4.10.5 Mechanical safety factors 12
4.11 Position indication 12
4.12 Optional equipment 13
4.12.1 Ancillaries 13
4.12.2 Manual operation 15
4.12.3 End stop adjustment 15

5 Conformity assessment 15
5.1 General 15
5.2 Type tests 16
5.3 Control of production process and quality system 16

6 Marking 17

7 Actuator selection guidelines 18

8 Documentation 18

Annex A (normative) Endurance test procedure 19

A.1 General 19
A.2 Test equipment 19
A.3 Test conditions 19
A.4 Test procedure 19
A.4.1 Design life 19
A.4.2 Output torque testing 19
A.4.3 Pressure testing 19
A.4.4 Hydraulic testing 20
A.5 Acceptance criteria 20

Annex B (informative) Actuator selection guidelines 21

B.1 General 21
B.2 Selection parameters 21
B.3 Actuator selection 22
B.3.1 General 22
B.3.2 Torque characteristics for rack and pinion or linear helical spline actuators 23
B.3.3 Torque characteristics for scotch yoke actuators (e.g. symmetric system) 24

Bibliography 25