

# DIN EN 12288:2010-10 (E)

## Industrial valves - Copper alloy gate valves

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>5</b>
<b>4</b>	<b>Requirements .....</b>	<b>6</b>
<b>4.1</b>	<b>Classification .....</b>	<b>6</b>
<b>4.1.1</b>	<b>Nominal sizes .....</b>	<b>6</b>
<b>4.1.2</b>	<b>Nominal size relationships .....</b>	<b>7</b>
<b>4.1.3</b>	<b>PN and Class designations .....</b>	<b>8</b>
<b>4.1.4</b>	<b>Valve series .....</b>	<b>9</b>
<b>4.2</b>	<b>Design .....</b>	<b>9</b>
<b>4.2.1</b>	<b>General .....</b>	<b>9</b>
<b>4.2.2</b>	<b>Materials .....</b>	<b>9</b>
<b>4.2.3</b>	<b>Pressure/temperature ratings .....</b>	<b>9</b>
<b>4.2.4</b>	<b>Dimensions .....</b>	<b>9</b>
<b>4.2.5</b>	<b>Operation .....</b>	<b>11</b>
<b>4.2.6</b>	<b>Auxiliary connections .....</b>	<b>12</b>
<b>4.3</b>	<b>Functional characteristics .....</b>	<b>12</b>
<b>4.3.1</b>	<b>Shell design strength .....</b>	<b>12</b>
<b>4.3.2</b>	<b>Obturator design strength .....</b>	<b>12</b>
<b>4.3.3</b>	<b>Shell tightness .....</b>	<b>12</b>
<b>4.3.4</b>	<b>Seat tightness .....</b>	<b>12</b>
<b>4.3.5</b>	<b>Flow characteristics .....</b>	<b>13</b>
<b>4.3.6</b>	<b>Sizing the operating element .....</b>	<b>14</b>
<b>5</b>	<b>Test procedures .....</b>	<b>14</b>
<b>5.1</b>	<b>Production pressure testing .....</b>	<b>14</b>
<b>5.2</b>	<b>Applicability of gas tests .....</b>	<b>15</b>
<b>5.3</b>	<b>Test durations .....</b>	<b>15</b>
<b>6</b>	<b>Declaration of compliance .....</b>	<b>15</b>
<b>7</b>	<b>Designation .....</b>	<b>15</b>
<b>8</b>	<b>Marking and preparation for storage and transportation .....</b>	<b>16</b>
<b>8.1</b>	<b>Required markings .....</b>	<b>16</b>
<b>8.1.1</b>	<b>Mandatory markings .....</b>	<b>16</b>
<b>8.1.2</b>	<b>Supplementary markings .....</b>	<b>16</b>
<b>8.1.3</b>	<b>Other markings .....</b>	<b>16</b>
<b>8.1.4</b>	<b>Omission of markings .....</b>	<b>17</b>
<b>8.2</b>	<b>Preparation for storage and transportation .....</b>	<b>17</b>
<b>8.2.1</b>	<b>Protection .....</b>	<b>17</b>
<b>8.2.2</b>	<b>Obturator position .....</b>	<b>17</b>
<b>8.2.3</b>	<b>Body ends .....</b>	<b>17</b>
<b>Annex A (normative)</b>	<b>Materials .....</b>	<b>18</b>
<b>Annex B (normative)</b>	<b>Pressure/temperature ratings .....</b>	<b>20</b>

<b>B.1</b>	<b>Valves with metallic body seats and obturator seats .....</b>	<b>20</b>
<b>B.2</b>	<b>Valves with non-metallic obturator seats and/or body seats .....</b>	<b>21</b>
	<b>Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC .....</b>	<b>22</b>
	<b>Bibliography .....</b>	<b>23</b>