DIN EN ISO 4126-4:2013-12 (E)

Safety devices for protection against excessive pressure - Part 4: Pilot operated safety valves (ISO 4126-4:2013)

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Symbols and units 8

5 Design 8
5.1 General 8
5.2 Valve end connections 9
5.3 Minimum requirements for springs 9
5.4 Materials 10

6 Production testing 10
6.1 Purpose 10
6.2 General 10
6.3 Hydrostatic testing 10
6.4 Pneumatic testing 11
6.5 Adjustment of set or cold differential test pressure 11
6.6 Seat leakage test 12
6.7 Pressure seals 12

7 Type testing 12
7.1 General 12
7.2 Tests to determine operating characteristics 13
7.3 Tests to determine flow characteristics 15
7.4 Determination of the coefficient of discharge 17
7.5 Certification of coefficient of discharge 17

8 Determination of pilot operated safety valve performance 17

9 Sizing of pilot operated safety valves 17

10 Marking and sealing 17
10.1 Marking 17
10.2 Sealing of a pilot operated safety valve 18

Annex ZA (informative) Relationship between this International Standard and the Essential Requirements of EU Directive 97/23/EC (PED) 19

Bibliography 20