

DIN EN ISO 4126-7:2013-12 (E)

Safety devices for protection against excessive pressure - Part 7: Common data (ISO 4126-7:2013)

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Symbols and units	6
5 Determination of safety valve performance	7
5.1 Determination of coefficient of discharge	7
5.2 Critical and subcritical flow	7
5.3 Discharge capacity at critical flow	7
5.4 Discharge capacity for any gas at subcritical flow	8
5.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	8
6 Sizing of safety valves	9
6.1 General	9
6.2 Valves for gas or vapour relief	9
6.3 Calculation of capacity	9
7 Thermodynamic properties	11
7.1 Steam data	11
7.2 Value of C as a function of k	11
7.3 Theoretical capacity correction factors for sub-critical flow (K_b)	11
7.4 Estimating chart for compressibility factor, Z	22
7.5 Capacity correction factor for viscosity, K_v	24
7.6 Properties of gases	25
8 Minimum requirements for helical compression springs	26
8.1 General	26
8.2 Materials	26
8.3 Marking	26
8.4 Dimensions	27
8.5 Spring plates/buttons	27
8.6 Inspection, testing and tolerances	27
9 Minimum requirements for safety valve disc springs	30
9.1 General	30
9.2 Materials	30
9.3 Marking	30
9.4 Dimensions	30
9.5 Inspection, testing and tolerances	30
Annex A (informative) Examples of capacity calculations for various media	31
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC (PED)	36
Bibliography	37