

DIN EN ISO 4126-7:2013-12 (E)

Safety devices for protection against excessive pressure - Part 7: Common data (ISO 4126-7:2013)

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Symbols and units	6
5	Determination of safety valve performance	7
5.1	Determination of coefficient of discharge	7
5.2	Critical and subcritical flow	7
5.3	Discharge capacity at critical flow	7
5.4	Discharge capacity for any gas at subcritical flow	8
5.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	8
6	Sizing of safety valves	9
6.1	General	9
6.2	Valves for gas or vapour relief	9
6.3	Calculation of capacity	9
7	Thermodynamic properties	11
7.1	Steam data	11
7.2	Value of C as a function of k	11
7.3	Theoretical capacity correction factors for sub-critical flow (K_b)	11
7.4	Estimating chart for compressibility factor, Z	22
7.5	Capacity correction factor for viscosity, K_v	24
7.6	Properties of gases	25
8	Minimum requirements for helical compression springs	26
8.1	General	26
8.2	Materials	26
8.3	Marking	26
8.4	Dimensions	27
8.5	Spring plates/buttons	27
8.6	Inspection, testing and tolerances	27
9	Minimum requirements for safety valve disc springs	30
9.1	General	30
9.2	Materials	30
9.3	Marking	30
9.4	Dimensions	30
9.5	Inspection, testing and tolerances	30
Annex A (informative)	Examples of capacity calculations for various media	31
Annex ZA (informative)	Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC (PED)	36
Bibliography		37