

# ISO 4126-4:2013-07 (E)

## Safety devices for protection against excessive pressure - Part 4: Pilot operated safety valves

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and units .....</b>	<b>5</b>
<b>5</b>	<b>Design .....</b>	<b>5</b>
5.1	General .....	5
5.2	Valve end connections .....	6
5.3	Minimum requirements for springs .....	6
5.4	Materials .....	7
<b>6</b>	<b>Production testing .....</b>	<b>7</b>
6.1	Purpose .....	7
6.2	General .....	7
6.3	Hydrostatic testing .....	7
6.4	Pneumatic testing .....	8
6.5	Adjustment of set or cold differential test pressure .....	8
6.6	Seat leakage test .....	9
6.7	Pressure seals .....	9
<b>7</b>	<b>Type testing .....</b>	<b>9</b>
7.1	General .....	9
7.2	Tests to determine operating characteristics .....	10
7.3	Tests to determine flow characteristics .....	12
7.4	Determination of the coefficient of discharge .....	14
7.5	Certification of coefficient of discharge .....	14
<b>8</b>	<b>Determination of pilot operated safety valve performance .....</b>	<b>14</b>
<b>9</b>	<b>Sizing of pilot operated safety valves .....</b>	<b>14</b>
<b>10</b>	<b>Marking and sealing .....</b>	<b>14</b>
10.1	Marking .....	14
10.2	Sealing of a pilot operated safety valve .....	15
Bibliography .....		16