DIN EN ISO 4126-7:2016-12 (E)

Safety devices for protection against excessive pressure - Part 7: Common data (ISO 4126-7:2013 + Amd 1:2016) (includes Amend ment A1:2016)

Contents

Page

1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Symbols and units 9
5 Determination of safety valve performance 10
5.1 Determination of coefficient of discharge 10
5.2 Critical and subcritical flow 10
5.3 Discharge capacity at critical flow 10
5.4 Discharge capacity for any gas at subcritical flow 11
5.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000 11
6 Sizing of safety valves 12
6.1 General 12
6.2 Valves for gas or vapour relief 12
6.3 Calculation of capacity 12
7 Thermodynamic properties 14
7.1 Steam data 14
7.2 Value of C as a function of k 14
7.3 Theoretical capacity correction factors for sub-critical flow (Kb) 14
7.4 Estimating chart for compressibility factor, Z 25
7.5 Capacity correction factor for viscosity, Kv 27
7.6 Properties of gases 28
8 Minimum requirements for helical compression springs 29
8.1 General 29
8.2 Materials 29
8.3 Marking 29
8.4 Dimensions 30
8.5 Spring plates/buttons 30
8.6 Inspection, testing and tolerances 30
9 Minimum requirements for safety valve disc springs 33
9.1 General 33
9.2 Materials 33
9.3 Marking 33
9.4 Dimensions 33
9.5 Inspection, testing and tolerances 33
Annex A (informative) Examples of capacity calculations for various media 34
A.1 Capacity calculations for gaseous media at critical flow (see 6.3.3.1) 34
A.2 Capacity calculations for gaseous media at subcritical flow (see 6.3.3.2) 36
A.3 Capacity calculations for liquids (see 6.3.4) 37

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 97/23/EC (PED) 39

Bibliography 40