

DIN EN 1111:2017-10 (E)

Sanitary tapware - Thermostatic mixing valves (PN 10) - General technical specification

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 6 |
| Introduction | | 7 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms and definitions | 9 |
| 4 | Symbols and units | 10 |
| 5 | Classification | 11 |
| 6 | Designation | 11 |
| 7 | Marking/identification | 12 |
| 7.1 | Marking | 12 |
| 7.2 | Identification | 12 |
| 8 | Materials | 12 |
| 8.1 | Chemical and hygiene requirements | 12 |
| 8.2 | Exposed surface condition and quality of coating | 12 |
| 9 | Dimensional characteristics | 13 |
| 9.1 | General remarks | 13 |
| 9.2 | Inlet dimensions | 13 |
| 9.3 | Outlet dimensions | 15 |
| 9.4 | Mounting dimensions | 17 |
| 9.5 | Special cases | 20 |
| 9.6 | Flexible hoses for outlet 2 | 20 |
| 9.7 | Outlet 2 | 20 |
| 10 | Backflow protection | 20 |
| 11 | Test sequence | 21 |
| 12 | Leaktightness | 21 |
| 12.1 | General | 21 |
| 12.1.1 | Principle | 21 |
| 12.1.2 | Apparatus | 21 |
| 12.2 | Leaktightness of the obturator and upstream thereof | 21 |
| 12.2.1 | General | 21 |
| 12.2.2 | Procedure | 21 |
| 12.2.3 | Requirements | 21 |
| 12.3 | Cross-flow between inlets | 22 |
| 12.3.1 | General | 22 |
| 12.3.2 | Procedure | 22 |
| 12.3.3 | Requirements | 22 |
| 12.4 | Leaktightness downstream of the obturator | 22 |
| 12.4.1 | Procedure | 22 |

| | | |
|--------|---|----|
| 12.4.2 | Requirements | 22 |
| 12.5 | Leaktightness of manually operated diverter | 22 |
| 12.5.1 | Procedure | 22 |
| 12.5.2 | Requirement | 23 |
| 12.6 | Leaktightness of diverters with automatic return | 23 |
| 12.6.1 | Procedure | 23 |
| 12.6.2 | Requirement | 23 |
| 13 | Performance | 23 |
| 13.1 | General | 23 |
| 13.1.1 | Initial settings | 23 |
| 13.1.2 | Apparatus | 24 |
| 13.1.3 | Procedure | 24 |
| 13.2 | Determination of flow rate | 25 |
| 13.2.1 | Principle | 25 |
| 13.2.2 | Procedure | 25 |
| 13.2.3 | Evaluation of the results | 26 |
| 13.2.4 | Requirements | 26 |
| 13.3 | Sensitivity | 26 |
| 13.3.1 | General | 26 |
| 13.3.2 | Principle | 26 |
| 13.3.3 | Procedure | 26 |
| 13.3.4 | Evaluation of results | 27 |
| 13.3.5 | Requirements | 27 |
| 13.4 | Fidelity | 28 |
| 13.4.1 | General | 28 |
| 13.4.2 | Principle | 28 |
| 13.4.3 | Procedure | 28 |
| 13.4.4 | Evaluation of results | 28 |
| 13.4.5 | Requirements | 28 |
| 13.5 | Temperature stability | 29 |
| 13.5.1 | Temperature control operation | 29 |
| 13.5.2 | Flow rate reduction | 29 |
| 13.5.3 | Cold supply failure and restoration | 30 |
| 13.5.4 | Supply pressure variation | 31 |
| 13.5.5 | Supply temperature variation | 32 |
| 13.5.6 | Temperature Override Stops | 32 |
| 14 | Pressure resistance | 33 |
| 14.1 | General | 33 |
| 14.2 | Apparatus | 33 |
| 14.3 | Testing of mechanical performance of the thermostatic mixing valve upstream of the obturator in the closed position | 33 |
| 14.3.1 | Procedure | 33 |
| 14.3.2 | Requirement | 33 |
| 14.4 | Mechanical behaviour downstream of the obturator - Obturator in the open position | 33 |
| 14.4.1 | Procedure | 33 |
| 14.4.2 | Requirement | 34 |
| 15 | Torsional resistance of the operating controls | 34 |
| 15.1 | General | 34 |
| 15.2 | Test method | 34 |
| 15.2.1 | Principle of the test | 34 |
| 15.2.2 | Apparatus | 34 |
| 15.2.3 | Procedure | 34 |
| 16 | Mechanical endurance characteristics | 35 |
| 16.1 | General | 35 |
| 16.2 | Endurance test for single sequential control device | 35 |
| 16.2.1 | Principle | 35 |
| 16.2.2 | Apparatus | 35 |
| 16.2.3 | Procedure | 35 |

| | | |
|--|---|----|
| 16.2.4 | Requirement | 36 |
| 16.3 | Endurance test for on/off flow control device operated by rotating the control handle | 36 |
| 16.3.1 | Principle | 36 |
| 16.3.2 | General | 36 |
| 16.4 | Endurance test for on/off flow control device, combined with diverter mechanism | 36 |
| 16.4.1 | Principle | 36 |
| 16.4.2 | Apparatus | 36 |
| 16.4.3 | Procedure | 36 |
| 16.4.4 | Requirement | 37 |
| 16.5 | Endurance test for other on-off flow control device | 37 |
| 16.5.1 | Principle | 37 |
| 16.5.2 | Apparatus | 37 |
| 16.5.3 | Procedure | 37 |
| 16.5.4 | Requirement | 37 |
| 16.6 | Mechanical endurance of diverters of thermostatic mixing valves | 38 |
| 16.6.1 | General | 38 |
| 16.6.2 | Test method | 38 |
| 16.6.3 | Requirements | 39 |
| 16.7 | Mechanical endurance of swivel spouts | 39 |
| 16.7.1 | General | 39 |
| 16.7.2 | Test method | 39 |
| 16.7.3 | Requirements | 40 |
| 16.8 | Thermal Element | 40 |
| 16.8.1 | Principle | 40 |
| 16.8.2 | Temperature adjustable valves (Type 1, 2, 4) | 40 |
| 16.8.3 | Temperature set valves (Type 5) | 41 |
| 16.8.4 | Other valves with special control devices (Type 6) | 41 |
| 17 | Acoustic characteristics | 42 |
| 17.1 | General | 42 |
| 17.2 | Procedure | 42 |
| 17.2.1 | Fitting and operating conditions for thermostatic mixing valves | 42 |
| 17.2.2 | Test method | 42 |
| 17.3 | Requirements | 42 |
| 17.3.1 | Expression of results | 42 |
| 17.3.2 | Determination of acoustic groups | 42 |
| 17.3.3 | Flow rate classes (thermostatic mixing valves Type 1, 2, 3) | 42 |
| Annex A (normative) Test Set-up Descriptions | | 44 |
| A.1 | General | 44 |
| A.2 | Inlet pipework | 44 |
| A.2.1 | Thermostat endurance | 44 |
| A.2.2 | Performance | 45 |
| A.3 | Outlet pipework | 45 |
| A.3.1 | General | 45 |
| A.3.2 | Outlet for valves without integral atmospheric discharge spouts | 46 |
| A.3.3 | Outlet for valves with atmospheric discharge nozzles | 48 |
| Annex B (normative) Measurements | | 49 |
| B.1 | Pressure | 49 |
| B.2 | Flow | 49 |
| B.3 | Temperature | 49 |
| B.3.1 | Mounting | 49 |
| B.3.2 | Accuracy | 49 |
| B.3.3 | Response time | 49 |
| B.4 | Angular position | 49 |
| B.5 | Duration of transients | 49 |
| Annex C (informative) Temperature transient | | 52 |

| | | |
|---|---|----|
| C.1 | Positive temperature transient | 52 |
| C.2 | Negative temperature transient | 53 |
| Annex D (informative) Acoustic classification (example) | | 54 |
| D.1 | Thermostatic mixing valve with nozzle | 54 |
| D.2 | Thermostatic mixing valves with shower or shower head outlet | 54 |
| D.3 | Thermostatic mixing valves with nozzle and shower or shower head outlet | 54 |
| Bibliography | | 56 |