

# DIN EN 816:2017-10 (E)

## Sanitary tapware - Automatic shut-off valves PN 10

---

| <b>Contents</b> |   | <b>Page</b> |
|-----------------|---|-------------|
|                 | European foreword .....   | 4           |
|                 | Introduction .....  | 5           |
| 1               | Scope .....   | 6           |
| 2               | Normative references .....  | 6           |
| 3               | Terms and definitions .....   | 7           |
| 4               | Designation .....   | 7           |
| 5               | Marking - Identification .....  | 7           |
| 5.1             | Marking .....   | 7           |
| 5.2             | Identification .....  | 8           |
| 6               | Materials .....   | 8           |
| 6.1             | Chemical and hygienic characteristics .....   | 8           |
| 6.2             | Exposed surface condition and quality of coating .....                                    | 8           |
| 7               | Backflow protection .....   | 8           |
| 8               | Dimensional characteristics .....   | 8           |
| 8.1             | General .....   | 8           |
| 8.2             | Tap with visible body for horizontal surfaces (see Figure 1 and Table 3) .....            | 9           |
| 8.3             | Taps with visible body for mounting on vertical surfaces (see Figure 2 and Table 4) ..... | 10          |
| 8.4             | In-line tapware with threaded inlet and outlet .....                                      | 10          |
| 8.4.1           | Inlets and outlets aligned (see Figure 3 and Table 5) .....                               | 10          |
| 8.4.2           | Inlets and outlets at right angles (see Figure 4 and Table 5) .....                       | 11          |
| 8.5             | Concealed tapware for vertical surfaces .....   | 11          |
| 8.6             | Mixer for horizontal surface (see Figures 5, 6 and 7 and Table 6) .....                   | 12          |
| 8.7             | Mixer with visible body for mounting on vertical surfaces .....                           | 16          |
| 8.7.1           | Mixers with parallel inlets .....   | 16          |
| 8.7.2           | Mixer with opposed inlets (see Figure 11 and Table 5) .....                               | 18          |
| 8.8             | Nozzle outlets for use with flow rate regulators .....                                    | 18          |
| 8.9             | Special cases .....   | 18          |
| 8.9.1           | Special taps and mixers for installation on horizontal surfaces .....                     | 18          |
| 8.9.2           | Special taps and mixers for installation on vertical surfaces .....                       | 19          |
| 9               | Leaktightness characteristics .....   | 19          |
| 9.1             | General .....   | 19          |
| 9.2             | Leaktightness tests .....   | 19          |
| 9.2.1           | Principle .....   | 19          |
| 9.2.2           | Apparatus .....   | 19          |
| 9.2.3           | Leaktightness of tapware upstream of the obturator .....                                  | 19          |
| 9.2.4           | Leaktightness of tapware downstream of the obturator with the obturator open .....        | 20          |
| 9.3             | Summary of the leaktightness tests .....  | 21          |
| 10              | Pressure resistance characteristics .....   | 22          |
| 10.1            | General .....   | 22          |
| 10.2            | Test of mechanical behaviour .....  | 22          |
| 10.2.1          | Principle .....   | 22          |

|        |   |    |
|--------|---|----|
| 10.2.2 | Apparatus .....   | 22 |
| 10.2.3 | Test of the mechanical behaviour upstream of the obturator, with the obturator in the closed position ..... | 22 |
| 10.2.4 | Test of mechanical behaviour downstream of the obturator, with the obturator in the open position .....     | 22 |
| 10.3   | Summary of the pressure tests .....   | 23 |
| 11     | Hydraulic characteristics .....   | 23 |
| 11.1   | General .....   | 23 |
| 11.2   | Test method .....   | 23 |
| 11.2.1 | Principle .....   | 23 |
| 11.2.2 | Test apparatus .....  | 23 |
| 11.2.3 | Mounting of single self-closing taps .....  | 26 |
| 11.2.4 | Mounting of mixers (see Figures 14 a), 14 b) and 14 c)) .....   | 26 |
| 11.3   | Principle of the flow test .....  | 27 |
| 11.4   | Requirements .....  | 28 |
| 11.4.1 | Flow rate .....   | 28 |
| 11.4.2 | Flow rate curve .....   | 28 |
| 11.4.3 | Flow duration .....   | 28 |
| 11.4.4 | Specific characteristics of mixers .....  | 29 |
| 11.4.5 | Testing at minimum pressure .....   | 31 |
| 12     | Mechanical properties - Operating force .....   | 31 |
| 12.1   | General .....   | 31 |
| 12.2   | Procedure .....   | 31 |
| 12.3   | Requirement .....   | 31 |
| 13     | Mechanical endurance or wear resistance characteristics .....   | 31 |
| 13.1   | General .....   | 31 |
| 13.2   | Procedure .....   | 31 |
| 13.3   | Cycle for a single tap .....  | 32 |
| 13.4   | Cycle for a mixer .....   | 32 |
| 13.5   | Minimum requirements .....  | 32 |
| 14     | Acoustic characteristics .....  | 33 |
| 14.1   | General .....   | 33 |
| 14.2   | Procedure .....   | 33 |
| 14.2.1 | Fitting and operating conditions for tapware .....  | 33 |
| 14.2.2 | Test method .....   | 33 |
| 14.3   | Requirements .....  | 33 |
| 14.3.1 | Expression of the results .....   | 33 |
| 14.3.2 | Determination of the acoustic group .....   | 33 |
| 14.3.3 | Flow class .....  | 34 |
|        | Annex A (normative) Pressure take off tees .....  | 35 |
|        | Annex B (informative) Acoustic classification (example) .....   | 37 |
| B.1    | Tapware with nozzle .....   | 37 |
| B.2    | Tapware with shower head outlet .....   | 37 |
| B.3    | Tapware with nozzle and shower or shower head outlet .....  | 37 |