

DIN EN 816:2017-10 (E)

Sanitary tapware - Automatic shut-off valves PN 10

Contents	Page
European foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Designation	7
5 Marking - Identification	7
5.1 Marking	7
5.2 Identification	8
6 Materials	8
6.1 Chemical and hygienic characteristics	8
6.2 Exposed surface condition and quality of coating	8
7 Backflow protection	8
8 Dimensional characteristics	8
8.1 General	8
8.2 Tap with visible body for horizontal surfaces (see Figure 1 and Table 3)	9
8.3 Taps with visible body for mounting on vertical surfaces (see Figure 2 and Table 4)	10
8.4 In-line tapware with threaded inlet and outlet	10
8.4.1 Inlets and outlets aligned (see Figure 3 and Table 5)	10
8.4.2 Inlets and outlets at right angles (see Figure 4 and Table 5)	11
8.5 Concealed tapware for vertical surfaces	11
8.6 Mixer for horizontal surface (see Figures 5, 6 and 7 and Table 6)	12
8.7 Mixer with visible body for mounting on vertical surfaces	16
8.7.1 Mixers with parallel inlets	16
8.7.2 Mixer with opposed inlets (see Figure 11 and Table 5)	18
8.8 Nozzle outlets for use with flow rate regulators	18
8.9 Special cases	18
8.9.1 Special taps and mixers for installation on horizontal surfaces	18
8.9.2 Special taps and mixers for installation on vertical surfaces	19
9 Leaktightness characteristics	19
9.1 General	19
9.2 Leaktightness tests	19
9.2.1 Principle	19
9.2.2 Apparatus	19
9.2.3 Leaktightness of tapware upstream of the obturator	19
9.2.4 Leaktightness of tapware downstream of the obturator with the obturator open	20
9.3 Summary of the leaktightness tests	21
10 Pressure resistance characteristics	22
10.1 General	22
10.2 Test of mechanical behaviour	22
10.2.1 Principle	22

10.2.2	Apparatus	22
10.2.3	Test of the mechanical behaviour upstream of the obturator, with the obturator in the closed position	22
10.2.4	Test of mechanical behaviour downstream of the obturator, with the obturator in the open position	22
10.3	Summary of the pressure tests	23
11	Hydraulic characteristics	23
11.1	General	23
11.2	Test method	23
11.2.1	Principle	23
11.2.2	Test apparatus	23
11.2.3	Mounting of single self-closing taps	26
11.2.4	Mounting of mixers (see Figures 14 a), 14 b) and 14 c))	26
11.3	Principle of the flow test	27
11.4	Requirements	28
11.4.1	Flow rate	28
11.4.2	Flow rate curve	28
11.4.3	Flow duration	28
11.4.4	Specific characteristics of mixers	29
11.4.5	Testing at minimum pressure	31
12	Mechanical properties - Operating force	31
12.1	General	31
12.2	Procedure	31
12.3	Requirement	31
13	Mechanical endurance or wear resistance characteristics	31
13.1	General	31
13.2	Procedure	31
13.3	Cycle for a single tap	32
13.4	Cycle for a mixer	32
13.5	Minimum requirements	32
14	Acoustic characteristics	33
14.1	General	33
14.2	Procedure	33
14.2.1	Fitting and operating conditions for tapware	33
14.2.2	Test method	33
14.3	Requirements	33
14.3.1	Expression of the results	33
14.3.2	Determination of the acoustic group	33
14.3.3	Flow class	34
Annex A (normative) Pressure take off tees	35	
Annex B (informative) Acoustic classification (example)	37	
B.1	Tapware with nozzle	37
B.2	Tapware with shower head outlet	37
B.3	Tapware with nozzle and shower or shower head outlet	37