

# DIN EN 1287:2017-10 (E)

## Sanitary tapware - Low pressure thermostatic mixing valves - General technical specification

---

Contents	Page
European foreword .....	6
Introduction .....	7
1 Scope .....	8
2 Normative references .....	8
3 Terms and definitions .....	9
4 Symbols and units .....	10
5 Classification .....	11
6 Designation .....	11
7 Marking/identification .....	12
7.1 Marking .....	12
7.2 Identification .....	12
8 Materials .....	12
8.1 Chemical and hygiene requirements .....	12
8.2 Exposed surface condition and quality of coating .....	12
9 Dimensional characteristics .....	12
9.1 General remarks .....	12
9.2 Inlet dimensions .....	12
9.3 Outlet dimensions .....	15
9.4 Mounting dimensions .....	17
9.5 Special cases .....	20
9.6 Flexible hoses for outlet 2 .....	20
9.7 Outlet 2 .....	20
10 Backflow protection .....	20
11 Test sequence .....	21
12 Leaktightness .....	21
12.1 General .....	21
12.1.1 Principle .....	21
12.1.2 Apparatus .....	21
12.2 Leaktightness of the obturator and upstream .....	21
12.2.1 General .....	21
12.2.2 Procedure .....	21
12.2.3 Requirements .....	21
12.3 Cross-flow between inlets .....	22
12.3.1 General .....	22
12.3.2 Procedure .....	22
12.3.3 Requirements .....	22
12.4 Leaktightness downstream of the obturator .....	22
12.4.1 Procedure .....	22

12.4.2	Requirements .....	22
12.5	Leaktightness of manually operated diverter .....	22
12.5.1	Procedure .....	22
12.5.2	Requirement .....	23
12.6	Leaktightness of diverter with automatic return .....	23
12.6.1	Procedure .....	23
12.6.2	Requirement .....	23
13	Performance .....	23
13.1	General .....	23
13.1.1	Initial settings .....	23
13.1.2	Apparatus .....	24
13.1.3	Procedure .....	24
13.2	Determination of flow rate .....	25
13.2.1	Principle .....	25
13.2.2	Procedure .....	25
13.2.3	Evaluation of the results .....	25
13.2.4	Requirements .....	25
13.3	Sensitivity .....	26
13.3.1	General .....	26
13.3.2	Principle .....	26
13.3.3	Procedure .....	26
13.3.4	Evaluation of results .....	26
13.3.5	Requirements .....	27
13.4	Fidelity .....	28
13.4.1	General .....	28
13.4.2	Principle .....	28
13.4.3	Procedure .....	28
13.4.4	Evaluation of results .....	28
13.4.5	Requirements .....	28
13.5	Temperature stability .....	29
13.5.1	Temperature control operation .....	29
13.5.2	Flow rate reduction .....	29
13.5.3	Cold supply failure and restoration .....	30
13.5.4	Supply pressure variation .....	31
13.5.5	Supply temperature variation .....	32
13.5.6	Temperature override stops .....	32
14	Pressure resistance .....	33
14.1	General .....	33
14.2	Apparatus .....	33
14.3	Testing of mechanical performance of the thermostatic mixing valve upstream of the obturator in the closed position .....	33
14.3.1	Procedure .....	33
14.3.2	Requirement .....	33
14.4	Mechanical behaviour downstream of the obturator - Obturator in the open position .....	34
14.4.1	Procedure .....	34
14.4.2	Requirement .....	34
15	Torsional resistance of the operating controls .....	34
15.1	General .....	34
15.2	Test method .....	34
15.2.1	Principle .....	34
15.2.2	Apparatus .....	34
15.2.3	Procedure .....	34
15.2.4	Requirements .....	35
16	Mechanical endurance characteristics .....	35
16.1	General .....	35
16.2	Endurance test for single sequential control device .....	35
16.2.1	Principle .....	35
16.2.2	Apparatus .....	35

<b>16.2.3</b>	<b>Procedure .....</b>	<b>36</b>
<b>16.2.4</b>	<b>Requirement .....</b>	<b>36</b>
<b>16.3</b>	<b>Endurance test for on/off flow control device operated by rotating the control handle .....</b>	<b>36</b>
<b>16.3.1</b>	<b>Principle .....</b>	<b>36</b>
<b>16.3.2</b>	<b>General .....</b>	<b>36</b>
<b>16.4</b>	<b>Endurance test for on/off flow control device, combined with diverter mechanism .....</b>	<b>36</b>
<b>16.4.1</b>	<b>Principle .....</b>	<b>36</b>
<b>16.4.2</b>	<b>Apparatus .....</b>	<b>36</b>
<b>16.4.3</b>	<b>Procedure .....</b>	<b>37</b>
<b>16.4.4</b>	<b>Requirement .....</b>	<b>37</b>
<b>16.5</b>	<b>Endurance test for other on-off flow control device .....</b>	<b>37</b>
<b>16.5.1</b>	<b>Principle .....</b>	<b>37</b>
<b>16.5.2</b>	<b>Apparatus .....</b>	<b>37</b>
<b>16.5.3</b>	<b>Procedure .....</b>	<b>37</b>
<b>16.5.4</b>	<b>Requirement .....</b>	<b>38</b>
<b>16.6</b>	<b>Mechanical endurance of diverters of thermostatic mixing valves .....</b>	<b>38</b>
<b>16.6.1</b>	<b>General .....</b>	<b>38</b>
<b>16.6.2</b>	<b>Test method .....</b>	<b>38</b>
<b>16.6.3</b>	<b>Requirements .....</b>	<b>39</b>
<b>16.7</b>	<b>Mechanical endurance of swivel of spouts .....</b>	<b>40</b>
<b>16.7.1</b>	<b>General .....</b>	<b>40</b>
<b>16.7.2</b>	<b>Test method .....</b>	<b>40</b>
<b>16.7.3</b>	<b>Requirements .....</b>	<b>40</b>
<b>16.8</b>	<b>Thermal element .....</b>	<b>40</b>
<b>16.8.1</b>	<b>Principle .....</b>	<b>40</b>
<b>16.8.2</b>	<b>Temperature adjustable valves, (Type 1, 2, 4) .....</b>	<b>41</b>
<b>16.8.3</b>	<b>Temperature set valves (Type 5) .....</b>	<b>41</b>
<b>16.8.4</b>	<b>Other valves with special control devices (Type 6) .....</b>	<b>42</b>
<b>Annex A (normative) Test set-up descriptions .....</b>		<b>43</b>
<b>A.1</b>	<b>General .....</b>	<b>43</b>
<b>A.2</b>	<b>Inlet pipework .....</b>	<b>43</b>
<b>A.2.1</b>	<b>Thermostat endurance .....</b>	<b>43</b>
<b>A.2.2</b>	<b>Performance .....</b>	<b>44</b>
<b>A.3</b>	<b>Outlet pipework .....</b>	<b>44</b>
<b>A.3.1</b>	<b>General .....</b>	<b>44</b>
<b>A.3.2</b>	<b>Outlet for valves except without integral atmospheric discharge spouts .....</b>	<b>44</b>
<b>Annex B (normative) Measurements .....</b>		<b>48</b>
<b>B.1</b>	<b>Pressure .....</b>	<b>48</b>
<b>B.2</b>	<b>Flow .....</b>	<b>48</b>
<b>B.3</b>	<b>Temperature .....</b>	<b>48</b>
<b>B.3.1</b>	<b>Mounting .....</b>	<b>48</b>
<b>B.3.2</b>	<b>Accuracy .....</b>	<b>48</b>
<b>B.3.3</b>	<b>Response time .....</b>	<b>48</b>
<b>B.4</b>	<b>Angular position .....</b>	<b>48</b>
<b>B.5</b>	<b>Duration of transients .....</b>	<b>48</b>
<b>Annex C (informative) Temperature transit .....</b>		<b>51</b>
<b>C.1</b>	<b>Positive temperature transient .....</b>	<b>51</b>
<b>C.2</b>	<b>Negative temperature transient .....</b>	<b>52</b>
<b>Annex D (normative) Hydraulic resistance for low pressure diverters with automatic return .....</b>		<b>53</b>
<b>Bibliography .....</b>		<b>55</b>