ISO 10434:2020 (E)

Bolted bonnet steel gate valves for the petroleum, petrochemical and allied industries

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Pressure/temperature ratings

5 Design

- 5.1 Body wall thickness
- 5.2 Bonnet wall thickness
- 5.3 Body dimensions
- 5.3.1 Flanged ends
- 5.3.2 Butt-welding ends
- 5.3.3 Body seats
- 5.4 Bonnet dimensions
- 5.5 Bonnet-to-body joint
- 5.6 Gate
- 5.7 Yoke
- 5.8 Stem and stem nut
- 5.9 Packing and packing box
- 5.10 Bolting
- 5.11 Operation
- 5.12 Auxiliary connections

6 Materials

- 6.1 Materials other than trim materials
- 6.2 Trim materials
- 6.3 Welding for fabrication and repair

7 Testing, inspection and examination

- 7.1 Pressure tests
- 7.1.1 General
- 7.1.2 Shell test
- 7.1.3 Closure tightness test
- 7.1.4 Optional backseat tightness test
- 7.1.5 Optional closure tightness test
- 7.1.6 Fugitive emission testing
- 7.2 Inspection
- 7.2.1 Extent of inspection
- 7.2.2 Site inspection
- 7.3 Examination
- 7.4 Supplementary examination

8 Marking

- 8.1 Legibility
- 8.2 Body marking
- 8.3 Ring joint marking
- 8.4 Identification plate marking

8.5 Special marking for unidirectional valves

9 Preparation for despatch

Annex A (informative) Information to be specified by the purchaser

Annex B (informative) Identification of valve terms

Annex C (informative) Valve material combinations

Page count: 38