

DIN EN 200:2024-05 (E)

Sanitary tapware - Single taps and combination taps for water supply systems of type 1 and type 2 - General technical specification

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 7 |
| Introduction | | 8 |
| 1 | Scope..... | 9 |
| 2 | Normative references..... | 11 |
| 3 | Terms and definitions..... | 12 |
| 4 | Designation | 15 |
| 5 | Marking and identification..... | 16 |
| 5.1 | Marking | 16 |
| 5.2 | Identification..... | 16 |
| 5.2.1 | Identification of inlets..... | 16 |
| 5.2.2 | Identification of flow controls equipment..... | 16 |
| 6 | Materials | 17 |
| 6.1 | Chemical and hygiene requirements..... | 17 |
| 6.2 | Exposed surface condition and quality of coating | 17 |
| 7 | Backflow protection..... | 17 |
| 8 | Sequence of testing..... | 17 |
| 9 | Dimensional characteristics | 17 |
| 9.1 | General remarks | 17 |
| 9.2 | Inlet dimensions..... | 18 |
| 9.3 | Outlet dimensions..... | 20 |
| 9.4 | Mounting dimensions..... | 24 |
| 9.5 | Special cases | 26 |
| 10 | Leaktightness characteristics..... | 27 |
| 10.1 | Principle..... | 27 |
| 10.2 | Apparatus | 27 |
| 10.3 | Leaktightness of the obturator and of the tap upstream of the obturator(s) with the obturator in the closed position..... | 27 |
| 10.3.1 | Procedure | 27 |
| 10.3.2 | Requirements..... | 27 |
| 10.4 | Leaktightness downstream of the obturator | 27 |
| 10.4.1 | General..... | 27 |
| 10.4.2 | Procedure | 27 |
| 10.4.3 | Requirements..... | 28 |
| 10.5 | Leaktightness of manually operated diverters..... | 28 |
| 10.5.1 | General..... | 28 |
| 10.5.2 | Procedure | 28 |
| 10.5.3 | Procedure where an outlet(s) cannot be artificially closed – products for type 1 systems | 28 |
| 10.5.4 | Procedure where an outlet(s) cannot be artificially closed – products for type 2 systems | 29 |
| 10.5.5 | Requirements..... | 29 |
| 10.6 | Leaktightness and operation of diverters with automatic return (and semi-automatic type diverters)..... | 29 |
| 10.6.1 | General..... | 29 |
| 10.6.2 | Procedure – products for Type 1 systems..... | 29 |

| | | |
|--------|---|----|
| 10.6.3 | Procedure – products for Type 2 systems | 30 |
| 10.6.4 | Requirements..... | 31 |
| 11 | Pressure resistance..... | 33 |
| 11.1 | Principle..... | 33 |
| 11.2 | Apparatus | 33 |
| 11.3 | Mechanical behaviour upstream of the obturator – obturator in the closed position..... | 33 |
| 11.3.1 | Procedure | 33 |
| 11.3.2 | Requirement..... | 33 |
| 11.4 | Mechanical behaviour downstream of the obturator – obturator in the open position..... | 33 |
| 11.4.1 | Procedure for products for type 1 systems..... | 33 |
| 11.4.2 | Procedure for products for type 2 systems..... | 33 |
| 11.4.3 | Requirement..... | 34 |
| 12 | Hydraulic performance | 34 |
| 12.1 | General | 34 |
| 12.2 | Determination of flow rate – products for type 1 systems | 35 |
| 12.2.1 | Principle..... | 35 |
| 12.2.2 | Apparatus | 35 |
| 12.2.3 | Procedure | 35 |
| 12.2.4 | Requirements..... | 35 |
| 12.3 | Determination of flow rate – products for type 2 systems | 36 |
| 12.3.1 | Principle..... | 36 |
| 12.3.2 | Apparatus | 36 |
| 12.3.3 | Procedure | 37 |
| 12.3.4 | Requirements..... | 37 |
| 13 | Mechanical strength/torsional resistance | 38 |
| 13.1 | Principle..... | 38 |
| 13.2 | Apparatus | 38 |
| 13.3 | Test piece..... | 38 |
| 13.4 | Procedure | 38 |
| 13.5 | Requirements..... | 38 |
| 14 | Mechanical endurance | 38 |
| 14.1 | General | 38 |
| 14.2 | Endurance test for on/off flow control devices operated by rotating the control handle..... | 39 |
| 14.2.1 | Principle..... | 39 |
| 14.2.2 | Apparatus | 39 |
| 14.2.3 | Procedure | 39 |
| 14.2.4 | Requirement..... | 41 |
| 14.3 | Endurance test for other on/off flow control devices | 42 |
| 14.3.1 | Principle..... | 42 |
| 14.3.2 | Apparatus | 42 |
| 14.3.3 | Procedure | 42 |
| 14.3.4 | Requirement..... | 42 |
| 14.4 | Endurance of manually operated diverters | 42 |
| 14.4.1 | Principle..... | 42 |
| 14.4.2 | Apparatus | 43 |
| 14.4.3 | Procedure | 43 |
| 14.4.4 | Requirement..... | 43 |
| 14.5 | Endurance of diverters with automatic return..... | 43 |
| 14.5.1 | Principle..... | 43 |
| 14.5.2 | Apparatus | 43 |
| 14.5.3 | Procedure | 44 |

| | |
|--|----|
| 14.5.4 Requirement..... | 44 |
| 14.6 Endurance test for swivel spouts | 45 |
| 14.6.1 Principle..... | 45 |
| 14.6.2 Apparatus | 45 |
| 14.6.3 Procedure for single outlet type..... | 45 |
| 14.6.4 Procedure for divided outlet type..... | 45 |
| 14.6.5 Requirements..... | 46 |
| 15 Acoustic characteristics — products for type 1 systems only | 47 |
| 15.1 General..... | 47 |
| 15.2 Procedure | 47 |
| 15.2.1 Flow rate class of sanitary tapware products (with appropriate acoustic information) .. | 47 |
| 15.2.2 Flow rate class of sanitary tapware products (without appropriate acoustic information) | 47 |
| 15.3 Expression of results | 47 |
| 15.3.1 Determination of acoustic group | 48 |
| 15.3.2 Correspondence between flow rate classes and measurements..... | 48 |
| Annex A (informative) Pressure take-off tee | 49 |
| Annex B (informative) Minimum flow rates and test pressures according to application | 52 |
| Annex C (informative) Product components (detailed by other standards)..... | 53 |
| Bibliography | 54 |

Figures

| | |
|---|----|
| Figure 1 — Supply system of Type 1 with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar] | 10 |
| Figure 2 — Supply system of Type 2 with a pressure range of (0,01 to 1,0) MPa [(0,1 to 10) bar] | 11 |
| Figure 3 — Bib taps 1/2 and 3/4 - single hole taps..... | 19 |
| Figure 4 — Multi hole combination taps | 20 |
| Figure 5 — Supply connections for taps and remote outlets | 20 |
| Figure 6 — Pillar and bib taps..... | 22 |
| Figure 7 — Remote outlet | 22 |
| Figure 8 — Single hole combination tap/remote outlet..... | 23 |
| Figure 9 — Bath/shower combination tap/remote outlet | 23 |
| Figure 10 — Single hole taps..... | 25 |
| Figure 11 — Two-hole tap (fixed centres)..... | 26 |
| Figure 12 — Three-hole tap (adjustable centres)..... | 26 |
| Figure 13 — Clamping Arrangement for use with ceramic sanitaryware..... | 26 |
| Figure 14 — Apparatus for testing the leaktightness of automatic diverters for taps for supply system of Type 2..... | 31 |
| Figure 15 — Flow rate test apparatus for sanitary tapware for Type 2 systems..... | 37 |
| Figure 16 — Life test -closing torque vs time..... | 41 |
| Figure 17 — Endurance test rig for divided-outlet swivel spout..... | 46 |
| Figure A.1 — Pressure take-off tee (test rig Type 1 taps) | 49 |
| Figure A.2 — Schematic examples of pressure take-off tees (test rig Type 1 taps) | 51 |

Tables

| | |
|---|-----------|
| Table 1 — Conditions of use | 9 |
| Table 2 — Designation | 15 |
| Table 3 — Sequence of testing | 17 |
| Table 4 — Inlet dimensions sanitary tapware | 18 |
| Table 5 — Outlet dimensions | 21 |
| Table 6 — Mounting dimensions | 24 |
| Table 7 — Informative summary of leaktightness tests | 32 |
| Table 8 — Informative summary of pressure resistance tests | 34 |
| Table 9 — Informative summary of test conditions for on/off flow control devices | 40 |
| Table 10 — Informative summary of test conditions for diverters | 44 |
| Table 11 — Informative summary of test conditions for swivel spout | 47 |
| Table 12 — Acoustic group | 48 |
| Table 13 — Flow rate classes (EN ISO 3822-4) | 48 |
| Table A.1 — Dimensions of the pressure take-off tee | 50 |
| Table B.1 — Recommended flow rates for domestic use | 52 |