

# DIN EN 817:2026-01 (E)

## Sanitary tapware - Mechanical mixing valves (PN 10) - General technical specifications (includes Corrigendum :2025)

---

| <b>Contents</b>  | <b>Page</b> |
|--|-------------|
| European foreword .....  | 5           |
| Introduction .....   | 6           |
| 1 Scope.....   | 7           |
| 2 Normative references.....  | 8           |
| 3 Terms and definitions.....   | 9           |
| 4 Designation .....  | 11          |
| 5 Marking and identification.....  | 12          |
| 5.1 Marking .....  | 12          |
| 5.2 Identification .....   | 12          |
| 6 Materials .....  | 13          |
| 6.1 Chemical and hygiene requirements .....  | 13          |
| 6.2 Exposed surface condition and quality of coating .....   | 13          |
| 7 Backflow protection.....   | 13          |
| 8 Sequence of testing.....   | 13          |
| 9 Dimensional characteristics .....  | 13          |
| 9.1 General remarks .....  | 13          |
| 9.2 Inlet dimensions.....  | 14          |
| 9.3 Outlet dimensions.....   | 15          |
| 9.4 Mounting dimensions.....   | 18          |
| 9.5 Special cases .....  | 19          |
| 10 Leaktightness characteristics.....  | 19          |
| 10.1 Principle .....   | 19          |
| 10.2 Apparatus .....   | 20          |
| 10.3 Leaktightness of the obturator and of the tap upstream of the obturator(s) with the obturator in the closed position..... | 20          |
| 10.4 Leaktightness downstream of the obturator.....  | 20          |
| 10.5 Leaktightness of manually operated diverters.....   | 21          |
| 10.6 Leaktightness and operation of diverters with automatic return (and semi-automatic type diverters) .....                  | 22          |
| 10.7 Cross flow between inlets .....   | 23          |
| 11 Pressure resistance.....  | 24          |
| 11.1 Principle .....   | 24          |
| 11.2 Apparatus .....   | 24          |
| 11.3 Mechanical behaviour upstream of the obturator - obturator in the closed position .....                                   | 24          |
| 11.4 Mechanical behaviour downstream of the obturator - obturator in the open position.....                                    | 25          |
| 12 Hydraulic Performance .....   | 25          |
| 12.1 General.....  | 25          |
| 12.2 Initial setting .....   | 26          |
| 12.3 Determination of flow rate .....  | 26          |
| 12.4 Determination of sensitivity.....   | 27          |

|             |  |           |
|-------------|--|-----------|
| <b>13</b>   | <b>Mechanical strength/torsional resistance .....</b>                              | <b>29</b> |
| <b>13.1</b> | <b>Principle.....</b>  | <b>29</b> |
| <b>13.2</b> | <b>Apparatus .....</b>   | <b>29</b> |
| <b>13.3</b> | <b>Procedure .....</b>   | <b>29</b> |
| <b>13.4</b> | <b>Requirements.....</b>   | <b>30</b> |
| <b>14</b>   | <b>Mechanical endurance.....</b>   | <b>30</b> |
| <b>14.1</b> | <b>General .....</b>   | <b>30</b> |
| <b>14.2</b> | <b>Endurance test of conventional control devices .....</b>                        | <b>30</b> |
| <b>14.3</b> | <b>Endurance test of joystick control devices.....</b>                             | <b>32</b> |
| <b>14.4</b> | <b>Endurance test of Single sequential control devices .....</b>                   | <b>34</b> |
| <b>14.5</b> | <b>Endurance test of separate controls .....</b>                                   | <b>36</b> |
| <b>14.6</b> | <b>Endurance test of diverter mechanisms .....</b>                                 | <b>38</b> |
| <b>14.7</b> | <b>Endurance test for swivel spouts.....</b>                                       | <b>40</b> |
| <b>15</b>   | <b>Acoustic characteristics .....</b>  | <b>41</b> |
| <b>15.1</b> | <b>General .....</b>   | <b>41</b> |
| <b>15.2</b> | <b>Procedure .....</b>   | <b>42</b> |
| <b>15.3</b> | <b>Expression of results .....</b>   | <b>42</b> |
|             | <b>Annex A (normative) Apparatus.....</b>  | <b>44</b> |
| <b>A.1</b>  | <b>General .....</b>   | <b>44</b> |
| <b>A.2</b>  | <b>Supply circuits .....</b>   | <b>44</b> |
| <b>A.3</b>  | <b>Test circuit .....</b>  | <b>45</b> |
| <b>A.4</b>  | <b>Pressure take off tees.....</b>   | <b>47</b> |
| <b>A.5</b>  | <b>Mounting of the mixing valve .....</b>  | <b>47</b> |
|             | <b>Annex B (informative) Pressure take-off tee.....</b>                            | <b>48</b> |
|             | <b>Annex C (informative) Recommended flow rates .....</b>                          | <b>51</b> |
|             | <b>Annex D (informative) Product components (detailed by other standards).....</b> | <b>52</b> |
|             | <b>Bibliography .....</b>  | <b>53</b> |

## **Figures**

|            |   |    |
|------------|---|----|
| Figure 1   | — Supply system of Type 1 with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar]..... | 8  |
| Figure 2   | — single hole taps.....   | 15 |
| Figure 3   | — Multi hole taps.....  | 15 |
| Figure 4   | — Remote outlet .....   | 16 |
| Figure 5   | — Single hole/remote outlet .....   | 17 |
| Figure 6   | — Bath/shower /remote outlet.....   | 17 |
| Figure 7   | — Single hole taps .....  | 19 |
| Figure 8   | — Clamping Arrangement for use with ceramic sanitaryware .....                              | 19 |
| Figure 9   | — Sensitivity curve .....   | 28 |
| Figure 10  | — Radius (r) for the determination of sensitivity.....                                      | 29 |
| Figure 11  | — Rectangular movement (One cycle 0 to 11) .....  | 31 |
| Figure 12  | — Test bench adjustment torque for conventional mixing valve.....                           | 32 |
| Figure 13  | — Triangular movement (One cycle 0 to 8).....   | 33 |
| Figure 14  | — Test bench adjustment torque for joystick mixing valve.....                               | 34 |
| Figure 15  | — linear movement (One cycle 0 to 6) .....  | 35 |
| Figure 16  | — Test bench adjustment torque for single sequential mixing valve.....                      | 36 |
| Figure A.1 | — Supply circuits.....  | 44 |

|   |    |
|---|----|
| Figure A.2 — Test circuit.....  | 46 |
| Figure A.3 — Mounting of the mixing valve.....  | 47 |
| Figure B.1 — Pressure take-off tee (test rig Type 1 taps).....                        | 48 |
| Figure B.2 — Schematic examples of pressure take-off tees (test rig Type 1 taps)..... | 49 |

**Tables**

|   |    |
|---|----|
| Table 1 — Conditions of use.....                                | 7  |
| Table 2 — Designation index.....                                | 11 |
| Table 3 — Sequence of testing.....                              | 13 |
| Table 4 — Inlet dimensions sanitary tapware.....                | 14 |
| Table 5 — Outlet dimensions.....                                | 16 |
| Table 6 — Mounting dimensions<Tbl_-></Tbl_->.....               | 18 |
| Table 7 — Informative summary of leaktightness tests.....       | 23 |
| Table 8 — Informative summary of pressure resistance tests..... | 25 |
| Table 9 — Initial settings.....                                 | 26 |
| Table 10 — Performance levels.....                              | 28 |
| Table 11 — Summary of test conditions for cartridges.....       | 38 |
| Table 12 — Summary of test conditions for diverters.....        | 40 |
| Table 13 — Summary of test conditions for swivel spout.....     | 41 |
| Table 14 — Acoustic group.....                                  | 42 |
| Table 15 — Flow rate classes (EN ISO 3822-4:1997, Annex A)..... | 43 |
| Table A.1 — Connecting dimensions.....                          | 46 |
| Table B.1 — Dimensions of the pressure take-off tee.....        | 48 |
| Table C.1 — Recommended flow rates.....                         | 51 |