

ISO 5211:2026-02 (E)

Industrial valves - Part-turn actuator attachments

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 Scope | | 1 |
| 2 Normative references | | 1 |
| 3 Terms and definitions | | 1 |
| 4 Maximum flange torques | | 2 |
| 5 Flange dimensions | | 2 |
| 6 Designation | | 5 |
| 7 Dimensions and torques | | 6 |
| 7.1 General..... | | 6 |
| 7.2 Drive by key(s)..... | | 6 |
| 7.3 Drive by parallel or diagonal square head..... | | 9 |
| 7.4 Drive by flat head..... | | 10 |
| 7.5 Drive by improved flat head..... | | 12 |
| 7.6 Drive by involute spline..... | | 13 |
| 7.7 Drive by bi-square..... | | 14 |
| 8 Position of driven components at interface below part-turn actuator | | 15 |
| 8.1 Drive by key(s)..... | | 15 |
| 8.2 Drive by parallel or diagonal square head or bi-square..... | | 17 |
| 8.3 Drive by flat head..... | | 18 |
| 9 Dowel pins | | 18 |
| Annex A (informative) Explanation of calculations | | 19 |
| Annex B (normative) Dimensions of keys and keyways | | 21 |
| Bibliography | | 27 |