DIN EN 1287:2026-07 (E)

Sanitary tapware - Low pressure thermostatic mixing valves - General technical specification

Contents

Page

European foreword 5

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 8

4 Symbols and units 9

5 Classification 10

6 Designation 10

7 Marking/identification 11
7.1 Marking 11
7.2 Identification 11

8 Materials 11
8.1 Chemical and hygiene requirements 11
8.2 Exposed surface condition and quality of coating 11

9 Dimensional characteristics 11
9.1 General remarks 11
9.2 Inlet dimensions 12
9.3 Outlet dimensions 14
9.4 Mounting dimensions 16
9.5 Special cases 19
9.6 Flexible hoses for outlet 2 19
9.7 Outlet 2 19

10 Backflow protection 19

11 Test sequence 20

12 Leaktightness 20
12.1 General 20
12.1.1 Principle 20
12.1.2 Apparatus 20
12.2 Leaktightness of the obturator and upstream thereof 20
12.2.1 General 20
12.2.2 Procedure 20
12.2.3 Requirements 20
12.3 Cross-flow between inlets 21
12.3.1 General 21
12.3.2 Procedure 21
12.3.3 Requirements 21
12.4 Leaktightness downstream of the obturator 21
12.4.1 General 21

12.4.2 Procedure 21
12.4.3 Requirements 21
12.5 Leaktightness of manually operated diverter 21
12.5.1 Procedure 21
12.5.2 Requirement 22
12.6 Leaktightness of diverter with automatic return 22
12.6.1 Procedure 22
12.6.2 Requirement 22

13 Performance 22
13.1 General 22
13.1.1 Initial settings 22
13.1.2 Apparatus 23
13.1.3 Procedure 23
13.2 Determination of flow rate 24
13.2.1 Principle 24
13.2.2 Procedure 24
13.2.3 Evaluation of the results 24
13.2.4 Requirements 25
13.3 Sensitivity 25
13.3.1 General 25
13.3.2 Principle 25
13.3.3 Procedure 25
13.3.4 Evaluation of results 25
13.3.5 Requirements 26
13.4 Fidelity 27
13.4.1 General 27
13.4.2 Principle 27
13.4.3 Procedure 27
13.4.4 Evaluation of results 27
13.4.5 Requirements 27
13.5 Temperature stability 28
13.5.1 Temperature control operation 28
13.5.2 Flow rate reduction 29
13.5.3 Cold supply failure and restoration 30
13.5.4 Supply pressure variation 31
13.5.5 Supply temperature variation 32
13.5.6 Temperature override stops 33

14 Pressure resistance 34
14.1 General 34
14.2 Apparatus 34
14.3 Testing of mechanical performance of the thermostatic mixing valve upstream of the obturator in the closed position 34
14.3.1 Procedure 34
14.3.2 Requirement 34
14.4 Mechanical behaviour downstream of the obturator - Obturator in the open position 35
14.4.1 Procedure 35
14.4.2 Requirement 35

15 Torsional resistance of the operating controls 35
15.1 Principle 35
15.2 Test method 35
15.2.1 Principle 35
15.2.2 Apparatus 35
15.2.3 Procedure 35
15.2.4 Requirements 36

16 Mechanical endurance characteristics 36
16.1 General 36
16.2 Endurance test for single sequential control device 36
16.2.1 Principle 36

16.2.2 Apparatus 36
16.2.3 Procedure 36
16.2.4 Requirement 37
16.3 Endurance test for on/off flow control device operated by rotating the control handle 37
16.3.1 Principle 37
16.3.2 General 37
16.4 Endurance test for on/off flow control device, combined with diverter mechanism 37
16.4.1 Principle 37
16.4.2 Apparatus 37
16.4.3 Procedure 37
16.4.4 Requirement 38
16.5 Endurance test for other on-off flow control device 38
16.5.1 Principle 38
16.5.2 Apparatus 38
16.5.3 Procedure 38
16.5.4 Requirement 39
16.6 Mechanical endurance of diverters of thermostatic mixing valves 39
16.6.1 General 39
16.6.2 Test method 39
16.6.3 Requirements 40
16.7 Mechanical endurance of swivel of spouts 40
16.7.1 General 40
16.7.2 Test method 40
16.7.3 Requirements 41
16.8 Thermal element 41
16.8.1 Principle 41
16.8.2 Temperature adjustable valves, (Type 1, 2, 4) 41
16.8.3 Temperature set valves (Type 5) 42
16.8.4 Other valves with special control devices (Type 6) 43

Annex A (normative) Test set-up descriptions 44

Annex B (informative) Measurements 50

Annex C (informative) Temperature transit 53

Annex D (normative) Hydraulic resistance for low pressure diverters with automatic return 55

Bibliography 57