

DIN EN 1287:2026-07 (E)

Sanitary tapware - Low pressure thermostatic mixing valves - General technical specification

Contents		Page
European foreword		5
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Symbols and units	9
5	Classification	10
6	Designation	10
7	Marking/identification	11
7.1	Marking	11
7.2	Identification	11
8	Materials	11
8.1	Chemical and hygiene requirements	11
8.2	Exposed surface condition and quality of coating	11
9	Dimensional characteristics	11
9.1	General remarks	11
9.2	Inlet dimensions	12
9.3	Outlet dimensions	14
9.4	Mounting dimensions	16
9.5	Special cases	19
9.6	Flexible hoses for outlet 2	19
9.7	Outlet 2	19
10	Backflow protection	19
11	Test sequence	20
12	Leaktightness	20
12.1	General	20
12.1.1	Principle	20
12.1.2	Apparatus	20
12.2	Leaktightness of the obturator and upstream thereof	20
12.2.1	General	20
12.2.2	Procedure	20
12.2.3	Requirements	20
12.3	Cross-flow between inlets	21
12.3.1	General	21
12.3.2	Procedure	21
12.3.3	Requirements	21
12.4	Leaktightness downstream of the obturator	21
12.4.1	General	21

12.4.2	Procedure	21
12.4.3	Requirements	21
12.5	Leaktightness of manually operated diverter	21
12.5.1	Procedure	21
12.5.2	Requirement	22
12.6	Leaktightness of diverter with automatic return	22
12.6.1	Procedure	22
12.6.2	Requirement	22
13	Performance	22
13.1	General	22
13.1.1	Initial settings	22
13.1.2	Apparatus	23
13.1.3	Procedure	23
13.2	Determination of flow rate	24
13.2.1	Principle	24
13.2.2	Procedure	24
13.2.3	Evaluation of the results	24
13.2.4	Requirements	25
13.3	Sensitivity	25
13.3.1	General	25
13.3.2	Principle	25
13.3.3	Procedure	25
13.3.4	Evaluation of results	25
13.3.5	Requirements	26
13.4	Fidelity	27
13.4.1	General	27
13.4.2	Principle	27
13.4.3	Procedure	27
13.4.4	Evaluation of results	27
13.4.5	Requirements	27
13.5	Temperature stability	28
13.5.1	Temperature control operation	28
13.5.2	Flow rate reduction	29
13.5.3	Cold supply failure and restoration	30
13.5.4	Supply pressure variation	31
13.5.5	Supply temperature variation	32
13.5.6	Temperature override stops	33
14	Pressure resistance	34
14.1	General	34
14.2	Apparatus	34
14.3	Testing of mechanical performance of the thermostatic mixing valve upstream of the obturator in the closed position	34
14.3.1	Procedure	34
14.3.2	Requirement	34
14.4	Mechanical behaviour downstream of the obturator - Obturator in the open position	35
14.4.1	Procedure	35
14.4.2	Requirement	35
15	Torsional resistance of the operating controls	35
15.1	Principle	35
15.2	Test method	35
15.2.1	Principle	35
15.2.2	Apparatus	35
15.2.3	Procedure	35
15.2.4	Requirements	36
16	Mechanical endurance characteristics	36
16.1	General	36
16.2	Endurance test for single sequential control device	36
16.2.1	Principle	36

16.2.2	Apparatus	36
16.2.3	Procedure	36
16.2.4	Requirement	37
16.3	Endurance test for on/off flow control device operated by rotating the control handle	37
16.3.1	Principle	37
16.3.2	General	37
16.4	Endurance test for on/off flow control device, combined with diverter mechanism	37
16.4.1	Principle	37
16.4.2	Apparatus	37
16.4.3	Procedure	37
16.4.4	Requirement	38
16.5	Endurance test for other on-off flow control device	38
16.5.1	Principle	38
16.5.2	Apparatus	38
16.5.3	Procedure	38
16.5.4	Requirement	39
16.6	Mechanical endurance of diverters of thermostatic mixing valves	39
16.6.1	General	39
16.6.2	Test method	39
16.6.3	Requirements	40
16.7	Mechanical endurance of swivel of spouts	40
16.7.1	General	40
16.7.2	Test method	40
16.7.3	Requirements	41
16.8	Thermal element	41
16.8.1	Principle	41
16.8.2	Temperature adjustable valves, (Type 1, 2, 4)	41
16.8.3	Temperature set valves (Type 5)	42
16.8.4	Other valves with special control devices (Type 6)	43
Annex A (normative) Test set-up descriptions		44
Annex B (informative) Measurements		50
Annex C (informative) Temperature transit		53
Annex D (normative) Hydraulic resistance for low pressure diverters with automatic return		55
Bibliography		57