

# DIN EN ISO 5211:2026-06 (E)

## Industrial valves - Part-turn actuator attachments (ISO 5211:2026)

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| <b>Foreword</b>  |  | <b>iv</b>   |
| <b>Introduction</b>  |  | <b>v</b>    |
| <b>1 Scope</b>   |  | <b>1</b>    |
| <b>2 Normative references</b>  |  | <b>1</b>    |
| <b>3 Terms and definitions</b>   |  | <b>1</b>    |
| <b>4 Maximum flange torques</b>  |  | <b>2</b>    |
| <b>5 Flange dimensions</b>   |  | <b>2</b>    |
| <b>6 Designation</b>   |  | <b>5</b>    |
| <b>7 Dimensions and torques</b>  |  | <b>6</b>    |
| 7.1 General  |  | 6           |
| 7.2 Drive by key(s)  |  | 6           |
| 7.3 Drive by parallel or diagonal square head                                |  | 9           |
| 7.4 Drive by flat head   |  | 10          |
| 7.5 Drive by improved flat head  |  | 12          |
| 7.6 Drive by involute spline   |  | 13          |
| 7.7 Drive by bi-square   |  | 14          |
| <b>8 Position of driven components at interface below part-turn actuator</b> |  | <b>15</b>   |
| 8.1 Drive by key(s)  |  | 15          |
| 8.2 Drive by parallel or diagonal square head or bi-square                   |  | 17          |
| 8.3 Drive by flat head   |  | 18          |
| <b>9 Dowel pins</b>  |  | <b>18</b>   |
| <b>Annex A (informative) Explanation of calculations</b>                     |  | <b>19</b>   |
| <b>Annex B (normative) Dimensions of keys and keyways</b>                    |  | <b>21</b>   |
| <b>Bibliography</b>  |  | <b>27</b>   |