

ISO 4126-4:2004-02 (E)

Safety devices for protection against excessive pressure - Part 4: Pilot-operated safety valves

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	6
5	Design	6
5.1	General	6
5.2	End connections	7
5.3	Minimum requirements for springs	9
5.4	Materials	9
6	Production testing	9
6.1	Purpose	9
6.2	General	9
6.3	Hydrostatic testing	9
6.4	Pneumatic testing	10
6.5	Adjustment of set or cold differential test pressure	11
6.6	Seat leakage test	11
6.7	Pressure seals	12
7	Type testing	12
7.1	General	12
7.2	Tests to determine operating characteristics	13
7.3	Tests to determine flow characteristics	15
7.4	Determination of the coefficient of discharge	16
7.5	Certification of coefficient of discharge	16
8	Determination of pilot operated safety valve performance	17
8.1	Determination of coefficient of discharge	17
8.2	Critical and subcritical flow	17
8.3	Discharge capacity at critical flow	17
8.4	Discharge capacity for any gas at subcritical flow	18
8.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	18
9	Sizing of pilot operated safety valves	18
9.1	General	18
9.2	Valves for gas or vapour relief	18
9.3	Calculation of capacity	19
10	Marking and sealing	20
10.1	Marking	20
10.2	Sealing of a pilot operated safety valve	21
Annex A (informative)	Examples of capacity calculations for various media	22
A.1	Capacity calculations for gaseous media at critical flow (see 9.3.3.1)	22
A.2	Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2)	24
A.3	Capacity calculations for liquids (see 9.3.4)	25