

# ISO 4126-4:2004-02 (E)

## Safety devices for protection against excessive pressure - Part 4: Pilot-operated safety valves

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Symbols and units .....	6
5	Design .....	6
5.1	General .....	6
5.2	End connections .....	7
5.3	Minimum requirements for springs .....	9
5.4	Materials .....	9
6	Production testing .....	9
6.1	Purpose .....	9
6.2	General .....	9
6.3	Hydrostatic testing .....	9
6.4	Pneumatic testing .....	10
6.5	Adjustment of set or cold differential test pressure .....	11
6.6	Seat leakage test .....	11
6.7	Pressure seals .....	12
7	Type testing .....	12
7.1	General .....	12
7.2	Tests to determine operating characteristics .....	13
7.3	Tests to determine flow characteristics .....	15
7.4	Determination of the coefficient of discharge .....	16
7.5	Certification of coefficient of discharge .....	16
8	Determination of pilot operated safety valve performance .....	17
8.1	Determination of coefficient of discharge .....	17
8.2	Critical and subcritical flow .....	17
8.3	Discharge capacity at critical flow .....	17
8.4	Discharge capacity for any gas at subcritical flow .....	18
8.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number $Re$ is equal to or greater than 80 000 .....	18
9	Sizing of pilot operated safety valves .....	18
9.1	General .....	18
9.2	Valves for gas or vapour relief .....	18
9.3	Calculation of capacity .....	19
10	Marking and sealing .....	20
10.1	Marking .....	20
10.2	Sealing of a pilot operated safety valve .....	21
Annex A (informative)	Examples of capacity calculations for various media .....	22
A.1	Capacity calculations for gaseous media at critical flow (see 9.3.3.1) .....	22
A.2	Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2) .....	24
A.3	Capacity calculations for liquids (see 9.3.4) .....	25