

ISO 4126-5:2004-03 (E)

Safety devices for protection against excessive pressure - Part 5: Controlled safety pressure relief systems (CSPRS)

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	7
5	Design	7
5.1	General	7
5.2	End connections	8
5.3	Minimum requirements for springs	8
5.4	Materials	8
5.5	Requirements and procedures	9
6	Production testing	9
6.1	Purpose	9
6.2	General	10
6.3	Hydrostatic testing	11
6.4	Pneumatic testing	12
6.5	Adjustment of cold differential test pressure	13
6.6	Seat leakage test	13
6.7	Pressure seals	13
7	Type testing	13
7.1	General	13
7.2	Tests to determine operating characteristics	15
7.3	Tests to determine flow characteristics	16
7.4	Records and test results	18
7.5	Determination of the coefficient of discharge	18
7.6	Certification of coefficient of discharge	18
7.7	Certification of CSPRS	18
8	Determination of CSPRS performance	18
8.1	Determination of coefficient of discharge	18
8.2	Critical and subcritical flow	18
8.3	Discharge capacity at critical flow	19
8.4	Discharge capacity for any gas at subcritical flow	19
8.5	Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000	20
9	Sizing of main valves	20
9.1	General	20
9.2	Valves for gas or vapour relief	20
9.3	Calculation of capacity	20
10	Marking and sealing	21
10.1	Marking on the shell of the main valve	21
10.2	Marking on an identification plate	21
10.3	Sealing of a CSPRS	22

Annex A (informative) Examples of sizing calculations for various fluids	23
A.1 Capacity calculations for gaseous media at critical flow (see 9.3.3.1)	23
A.2 Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2)	25
A.3 Capacity calculations for liquids (see 9.3.4)	26