

ISO 4126-5:2004-03 (E)

Safety devices for protection against excessive pressure - Part 5: Controlled safety pressure relief systems (CSPRS)

	Contents	Page
Foreword		v
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Symbols and units		7
5 Design		7
5.1 General		7
5.2 End connections		8
5.3 Minimum requirements for springs		8
5.4 Materials		8
5.5 Requirements and procedures		9
6 Production testing		9
6.1 Purpose		9
6.2 General		10
6.3 Hydrostatic testing		11
6.4 Pneumatic testing		12
6.5 Adjustment of cold differential test pressure		13
6.6 Seat leakage test		13
6.7 Pressure seals		13
7 Type testing		13
7.1 General		13
7.2 Tests to determine operating characteristics		15
7.3 Tests to determine flow characteristics		16
7.4 Records and test results		18
7.5 Determination of the coefficient of discharge		18
7.6 Certification of coefficient of discharge		18
7.7 Certification of CSPRS		18
8 Determination of CSPRS performance		18
8.1 Determination of coefficient of discharge		18
8.2 Critical and subcritical flow		18
8.3 Discharge capacity at critical flow		19
8.4 Discharge capacity for any gas at subcritical flow		19
8.5 Discharge capacity for non-flashing liquid as the test medium in the turbulent zone where the Reynolds number Re is equal to or greater than 80 000		20
9 Sizing of main valves		20
9.1 General		20
9.2 Valves for gas or vapour relief		20
9.3 Calculation of capacity		20
10 Marking and sealing		21
10.1 Marking on the shell of the main valve		21
10.2 Marking on an identification plate		21
10.3 Sealing of a CSPRS		22

Annex A (informative) Examples of sizing calculations for various fluids	23
A.1 Capacity calculations for gaseous media at critical flow (see 9.3.3.1)	23
A.2 Capacity calculations for gaseous media at subcritical flow (see 9.3.3.2)	25
A.3 Capacity calculations for liquids (see 9.3.4)	26