

# ISO 17292:2004-08 (E)

## Metal ball valves for petroleum, petrochemical and allied industries

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>3</b>
<b>4</b>	<b>Pressure/temperature ratings .....</b>	<b>3</b>
<b>4.1</b>	<b>Valve rating .....</b>	<b>3</b>
<b>4.2</b>	<b>Shell rating .....</b>	<b>3</b>
<b>4.3</b>	<b>Seat and seal rating .....</b>	<b>4</b>
<b>5</b>	<b>Design .....</b>	<b>4</b>
<b>5.1</b>	<b>Flow passageway .....</b>	<b>4</b>
<b>5.2</b>	<b>Body .....</b>	<b>5</b>
<b>6</b>	<b>Materials .....</b>	<b>13</b>
<b>6.1</b>	<b>Shell .....</b>	<b>13</b>
<b>6.2</b>	<b>Shell material repair .....</b>	<b>13</b>
<b>6.3</b>	<b>Trim .....</b>	<b>13</b>
<b>6.4</b>	<b>Identification plate .....</b>	<b>13</b>
<b>6.5</b>	<b>Bolting .....</b>	<b>13</b>
<b>6.6</b>	<b>Seals .....</b>	<b>14</b>
<b>6.7</b>	<b>Threaded plugs .....</b>	<b>14</b>
<b>6.8</b>	<b>Low temperature service .....</b>	<b>14</b>
<b>7</b>	<b>Marking .....</b>	<b>14</b>
<b>7.1</b>	<b>Legibility .....</b>	<b>14</b>
<b>7.2</b>	<b>Body marking .....</b>	<b>14</b>
<b>7.3</b>	<b>Ring joint marking .....</b>	<b>15</b>
<b>7.4</b>	<b>Identification plate .....</b>	<b>15</b>
<b>7.5</b>	<b>Special marking for unidirectional valves .....</b>	<b>15</b>
<b>8</b>	<b>Testing and inspection .....</b>	<b>15</b>
<b>8.1</b>	<b>Pressure tests .....</b>	<b>15</b>
<b>8.2</b>	<b>Inspection .....</b>	<b>17</b>
<b>8.3</b>	<b>Examination .....</b>	<b>17</b>
<b>8.4</b>	<b>Supplementary examination .....</b>	<b>18</b>
<b>9</b>	<b>Preparation for despatch .....</b>	<b>18</b>
<b>Annex A (informative) Information to be specified by the purchaser .....</b>		<b>19</b>
<b>Annex B (informative) Identification of valve parts .....</b>		<b>20</b>
<b>Bibliography .....</b>		<b>22</b>