

DIN EN 13433:2006-05 (E)

Devices to prevent pollution by backflow of potable water - Mechanical disconnecter, direct actuated - Family G, type A

| Contents | | Page |
|----------------------------------------------------------------------|--|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 Scope | | 5 |
| 2 Normative references | | 5 |
| 3 Terms and definitions | | 6 |
| 4 Nominal size | | 7 |
| 5 Designation | | 8 |
| 6 Symbolization | | 8 |
| 7 Physico-chemical characteristics | | 8 |
| 7.1 Materials | | 8 |
| 7.2 Nature of the materials | | 9 |
| 8 Design | | 9 |
| 8.1 General | | 9 |
| 8.2 Relief valve | | 9 |
| 8.3 Disconnection distance | | 10 |
| 9 Characteristics and tests | | 10 |
| 9.1 General | | 10 |
| 9.2 General tolerances | | 10 |
| 9.3 Expression of the results | | 11 |
| 9.4 Dimensional characteristics | | 11 |
| 9.5 Mechanical characteristics | | 12 |
| 9.6 Leaktightness characteristics | | 15 |
| 9.7 Hydraulic characteristics | | 18 |
| 10 Order of testing | | 23 |
| 11 Marking and technical documents | | 23 |
| 11.1 General | | 23 |
| 11.2 Marking | | 23 |
| 11.3 Technical documents | | 24 |
| 12 Presentation at delivery | | 25 |
| Annex A (informative) Examples of presentation of test results | | 26 |
| Bibliography | | 28 |