

E DIN 4630:2021-02 (E)

Erscheinungsdatum: 2021-01-15

Road vehicles - Data parameter specification for body application units in commercial vehicles

| Inhalt | Seite |
|-----------------------------------------------------------------------------|-------|
| Foreword | 6 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions..... | 8 |
| 4 Symbols and abbreviations..... | 9 |
| 5 Definition of use cases | 10 |
| 5.1 General use cases | 10 |
| 5.2 Examples of network-architecture | 11 |
| 5.3 BAU sub-parts..... | 11 |
| 6 Specification of parameters | 12 |
| 6.1 Parameter attributes..... | 12 |
| 6.2 Detailed specification of generic parameters | 12 |
| 6.2.1 General..... | 12 |
| 6.2.2 Error code | 13 |
| 6.2.3 Alarm code..... | 13 |
| 6.2.4 Commercial vehicle status..... | 14 |
| 6.2.5 Vehicle lowering status | 14 |
| 6.2.6 Vehicle load | 15 |
| 6.3 Detailed specification of general ECU parameters | 15 |
| 6.3.1 General..... | 15 |
| 6.3.2 ECU input voltage | 15 |
| 6.3.3 ECU temperature | 16 |
| 6.3.4 CPU temperature | 16 |
| 6.3.5 Vehicle type | 16 |
| 6.3.6 Implemented logical entities | 17 |
| 6.4 Detailed specification of TGU parameters..... | 17 |
| 6.5 Detailed specification of IGU parameters..... | 18 |
| 6.5.1 General..... | 18 |
| 6.5.2 ISO 11992 parameters | 18 |
| 6.5.3 CiA 413-5 parameters | 18 |
| 6.5.4 J1939 parameters..... | 18 |
| 6.6 Detailed specification of the FMU parameters..... | 18 |
| 6.6.1 General..... | 18 |
| 6.7 Detailed specification of general BAU parameters..... | 18 |
| 6.7.1 General..... | 18 |
| 6.7.2 BAU type..... | 18 |
| 6.7.3 BAU sub-type..... | 19 |
| 6.7.4 Next maintenance day..... | 19 |
| 6.7.5 Next maintenance month..... | 19 |
| 6.7.6 Next maintenance year..... | 20 |
| 6.8 Detailed specification of generic BAU and BAU sub-part parameters | 20 |
| 6.8.1 General..... | 20 |
| 6.8.2 BAU or BAU sub-part..... | 20 |
| 6.8.3 BAU or BAU sub-part mode | 20 |
| 6.8.4 BAU or sub-part mounting location..... | 21 |

| | | |
|--------|---------------------------------------------------|----|
| 6.8.5 | BAU or sub-part status..... | 21 |
| 6.8.6 | BAU or sub-part enable status | 22 |
| 6.8.7 | BAU or sub-part position status | 23 |
| 6.8.8 | BAU or sub-part moving status | 23 |
| 6.8.9 | Operating hours..... | 23 |
| 6.8.10 | Resettable operating hours..... | 24 |
| 6.8.11 | Operating cycles | 24 |
| 6.8.12 | Resettable operating cycles | 25 |
| 6.8.13 | Remaining operating hours | 25 |
| 6.8.14 | Hydraulic oil pressure | 25 |
| 6.8.15 | Hydraulic oil level | 26 |
| 6.8.16 | Hydraulic oil temperature..... | 26 |
| 6.8.17 | Chain emergency-stop status | 26 |
| 6.8.18 | Windshield wiper control request..... | 27 |
| 7 | Specification of BAU specific parameters..... | 28 |
| 7.1 | General | 28 |
| 7.2 | Lifting units (LU)..... | 28 |
| 7.2.1 | General | 28 |
| 7.2.2 | LU categories | 28 |
| 7.2.3 | Transport position status | 28 |
| 7.2.4 | Vehicle-mounted crane unit (VMCU) | 29 |
| 7.2.5 | Tail-lift unit (TLU)..... | 29 |
| 7.3 | Heating and refrigerating unit (HRU)..... | 33 |
| 7.3.1 | General | 33 |
| 7.3.2 | HRU classes | 33 |
| 7.3.3 | HRU compartment number | 34 |
| 7.3.4 | HRU temperature setpoint command..... | 34 |
| 7.3.5 | HRU return air temperature..... | 35 |
| 7.3.6 | HRU supply air temperature | 35 |
| 7.3.7 | HRU evaporator temperature | 35 |
| 7.3.8 | HRU compartment temperature setpoint status | 36 |
| 7.3.9 | HRU status | 36 |
| 7.3.10 | HRU ambient temperature..... | 36 |
| 7.3.11 | HRU battery voltage | 37 |
| 7.3.12 | HRU diesel operating hours..... | 37 |
| 7.3.13 | HRU electrical operating hours | 37 |
| 7.3.14 | HRU total operating hours | 38 |
| 7.3.15 | HRU functionality and mode..... | 38 |
| 7.4 | Refuse collecting unit (RCU) | 39 |
| 7.4.1 | General | 39 |
| 7.4.2 | RCU categories..... | 39 |
| 7.4.3 | RCU compliant to EN 16815 | 40 |
| 7.4.4 | Classes of RCU compliant to EN 16815 | 40 |
| 7.5 | Container unit (CU)..... | 41 |
| 7.5.1 | General | 41 |
| 7.5.2 | Categories of CUs | 41 |
| 7.5.3 | General CU parameters | 42 |
| 7.5.4 | CU status..... | 43 |
| 7.5.5 | Closure elements states | 43 |
| 7.6 | Tipper unit (TU) | 44 |
| 7.6.1 | General | 44 |
| 7.6.2 | Categories of TUs..... | 44 |
| 7.6.3 | Temperature of loaded material..... | 44 |
| 7.6.4 | Tipper inclination in x-axis..... | 45 |
| 7.6.5 | Tipper inclination in y-axis..... | 45 |
| 7.7 | Fire-fighting unit (FFU) | 45 |
| 7.7.1 | General | 45 |

| | | |
|---------------------|-------------------------------------------------------------------------------------------|-----------|
| 7.7.2 | Categories of FFUs | 45 |
| 7.7.3 | Specific FFU parameters..... | 45 |
| Annex A | (normative) Parameter mapping to SAE J1939-based networks | 46 |
| A.1 | Mapping of the application layer..... | 46 |
| A.1.1 | General..... | 46 |
| A.1.2 | Overview on general PGs | 46 |
| A.1.3 | Overview on PGs transmitted by LUs..... | 51 |
| A.1.4 | Overview on PGs transmitted by HRUs | 51 |
| A.1.5 | Overview on PGs transmitted by RCUs..... | 51 |
| A.1.6 | Overview on PGs f transmitted by CUs | 51 |
| A.1.7 | Overview on PGs transmitted by TUs | 51 |
| A.1.8 | Overview on PGs transmitted by FFUs..... | 52 |
| A.2 | Detailed specification of general PGs..... | 52 |
| A.2.1 | Alarms (ALARM) | 52 |
| A.2.2 | Acoustic warning request (AWR)..... | 52 |
| A.2.3 | Acoustic warning states (AWS) | 53 |
| A.2.4 | Vehicle load (AXL)..... | 53 |
| A.2.5 | Body application unit 1 (BAU1) | 54 |
| A.2.6 | Body application unit 2 (BAU2) | 54 |
| A.2.7 | Body application unit 3 (BAU3) | 55 |
| A.2.8 | Body application unit 4 (BAU4) | 56 |
| A.2.9 | Body application unit 5 (BAU5) | 56 |
| A.2.10 | Body application unit 6 (BAU6) | 57 |
| A.2.11 | Body application unit 7 (BAU7) | 58 |
| A.2.12 | Body application unit 8 (BAU8) | 58 |
| A.2.13 | Electronic control unit (ECU)..... | 59 |
| A.2.14 | ECU power supply (ECU_PWR) | 59 |
| A.2.15 | ECU temperatures (ECU_TMP)..... | 60 |
| A.2.16 | Error information (ERROR) | 60 |
| A.2.17 | Heating and refrigerating unit 1 (HRU1)..... | 61 |
| A.2.18 | Heating and refrigerating unit 2 (HRU2)..... | 62 |
| A.2.19 | Heating and refrigerating unit 3 (HRU3)..... | 62 |
| A.2.20 | Heating and refrigerating unit 4 (HRU4)..... | 63 |
| A.2.21 | HRU temperature setpoint (HTS)..... | 63 |
| A.2.22 | Lifting unit (LU1) | 64 |
| A.2.23 | Tail-lift unit 1 (TLU1) | 65 |
| A.2.24 | Vehicle status (VS) | 65 |
| A.2.25 | Windshield wiper request (WWR)..... | 66 |
| A.3 | Transport layer protocol specification | 66 |
| A.4 | Data link layer protocol requirements..... | 66 |
| A.5 | Physical layer requirements..... | 67 |
| A.5.1 | General requirements..... | 67 |
| A.5.2 | Connector requirements..... | 67 |
| A.6 | Additional requirements | 67 |
| A.6.1 | Address claiming | 67 |
| A.6.2 | Sleep and wake-up handling..... | 67 |
| Annex B | (normative) Parameter mapping to EN 50325-4 (CANopen) communication networks | 68 |
| B.1 | CANopen specific parameter attributes..... | 68 |
| B.1.1 | General..... | 68 |
| B.2 | Mapping to the application layer | 68 |
| B.2.1 | Overview | 68 |
| B.2.2 | Pre-defined PDOs | 70 |
| B.3 | Transport layer protocol requirements | 70 |
| B.4 | Data link layer protocol requirements..... | 70 |
| B.5 | Physical layer requirements..... | 70 |
| Bibliography | | 71 |